TOWN OF DURHAM ELECTRICAL PERMIT APPLICATION

Property Location						_ Date		
Property Owner's Name								
	NameCell Phone:							
Company Name & Address								
Add(C33								
Master Electrician #		F						
(Journeymen must have letter								
Use: (check one) Residential			•	•	-			
Wiring Method: (check one) N								
Type of Installation: (check one)				_			Ren	
					Laim			
Services, Panels, and/or	Qty							
Disconnects	Qty		Devices	Qty	F	ixtures	Qty	
			Receptacles		- II	ncandescent		
100			Switches		L	ED		
200			Motion Sensor		F	luorescent		
400			Other		Ν	leon		
800					S	moke Detector/CO		
1000			Transformers	Qty	(See info on back)		
1200			Up to 25 KVA		E	xit/Emergency Lts.		
1600			25 KVA &		E	xh/Paddle Fan		
Meters			Over					
Motors			Equipment		Qty		Qty	
Air Compressor/Condenser			Range/Cooktop)		Washer		
Electric Heat			Wall Oven			Dryer		
Heat Pump			Microwave			, Boiler Gas/Oil		
Pre-Mfgd/Temp Site Trlr			Dishwasher			Furnace Gas/Oil		
Modular Homes			Disposal			A/C Unit		
Fire Pump			HW Heater			Door Openers		
Temp Service (\$10 fee)			Refrigerator/Fr	eezer		Sump Pump		
Illuminated Sign							-	
Above Ground Pool/Hot Tub)		Generators &		Qty	PV Solar System	Qty	
In Ground Pool			Transfer Switch	nes		Roof Mount		
			Up to 10 KVA			Ground Mount		
ated Cost of Construction: \$			10 KVA to 75 K	/A		Tracker System		
mount: \$ < # Cash			Over 75 KVA			PV Panels		
< # Cash	_		Transfer Switch	es		Mounting Rail		
						Inverters	<u> </u>	
iption of Work:						Disconnects	-	
						Combiner Boxes		
						Meters		

Applicant certifies that all information given is correct and that he/she will comply with the current NEC Building Code and Energy Code along with any other applicable State or Town Ordinances.

Smoke alarms shall be provided in dwelling units.

R314.2.2 Alterations, repairs and additions.

Where alterations, repairs or additions requiring a permit occur, or where one or more sleeping rooms are added or created in existing dwellings, the individual dwelling unit shall be equipped with smoke alarms located as required for new dwellings.

Exceptions:

1.Work involving the exterior surfaces of dwellings, such as the replacement of roofing or siding, the addition or replacement of windows or doors, or the addition of a porch or deck, are exempt from the requirements of this section.

2.Installation, alteration or repairs of plumbing or mechanical systems are exempt from the requirements of this section.

R314.3.1 Installation near cooking appliances.

Smoke alarms shall not be installed in the following locations unless this would prevent placement of a smoke alarm in a location required by Section R314.3.

1. Ionization smoke alarms shall not be installed less than 20 feet (6096 mm) horizontally from a permanently installed cooking appliance.

2. Ionization smoke alarms with an alarm-silencing switch shall not be installed less than 10 feet (3048 mm) horizontally from a permanently installed cooking appliance.

3.Photoelectric smoke alarms shall not be installed less than 6 feet (1828 mm) horizontally from a permanently installed cooking appliance.

R314.4 Interconnection.

Where more than one smoke alarm is required to be installed within an individual dwelling unit in accordance with Section R314.3, the alarm devices shall be interconnected in such a manner that the actuation of one alarm will activate all of the alarms in the individual dwelling unit. Physical interconnection of smoke alarms shall not be required where listed wireless alarms are installed and all alarms sound upon activation of one alarm. Exception: Interconnection of smoke alarms in existing areas shall not be required where alterations or repairs do not result in removal of interior wall or ceiling finishes exposing the structure, unless there is an attic, crawl space or basement available that could provide access for interconnection without the removal of interior finishes.

R314.5 Combination alarms.

Combination smoke and carbon monoxide alarms shall be permitted to be used in lieu of smoke alarms.

R314.6 Power source.

Smoke alarms shall receive their primary power from the building wiring where such wiring is served from a commercial source and, where primary power is interrupted, shall receive power from a battery. Wiring shall be permanent and without a disconnecting switch other than those required for overcurrent protection. Exceptions:

1.Smoke alarms shall be permitted to be battery operated where installed in buildings without commercial power.

2.Smoke alarms installed in accordance with Section R314.2.2 shall be permitted to be battery powered.