

MILL POND NUTRIENT CONTROL MEASURES *FINAL REPORT*

Project:

for the Durham, NH Mill Pond Study

Prepared for:

**Todd I. Selig, Town Administrator
April Talon, Town Engineer
Town of Durham
8 Newmarket Road
Durham, NH 03824**

Prepared by:

**Robert Roseen, PE, PhD, D.WRE and Jake Sahl, WS
Waterstone Engineering, PLLC
9 Gretas Way, Stratham, NH 03885**

Project Manager:

**Jeffrey C. Provost, P.E.
Weston & Sampson
100 International Dr., Suite 152
Portsmouth, NH 03801**

November 30, 2018



**WATERSTONE
ENGINEERING**
INNOVATIVE STORMWATER MANAGEMENT



Weston & SampsonSM

TABLE OF CONTENTS

1.	Summary	1
2.	Mill Pond Background and Regional Context	2
A.	Environmental Impacts from Growth	2
B.	2017 NH Small MS4 Permit	3
C.	EPA Integrated Planning Framework and Watershed Based Planning.....	3
D.	2014 Mill Pond Assessment.....	4
3.	Watershed Assessment.....	5
4.	Nitrogen Source Identification Reporting.....	13
5.	Stormwater Management and Retrofit Opportunities.....	17
6.	BMP Optimization for Nitrogen Removal.....	17
A.	BMP Optimization Examples at the BMP and Land Use Scale	18
B.	BMP Optimization and Effective Impervious Cover Reduction in the Mill Pond Watershed	19
7.	Implementation Schedule.....	22
A.	Scheduling and Cost Considerations for Mill Pond.....	22
B.	Guidance for Developing Implementation Schedules.....	23
8.	BMP Examples for Nutrient Control in Urban Areas.....	24
9.	BMP Implementation Examples for Mill Pond	26
A.	Design and Maintenance	26
B.	Pollutant Load Reduction.....	26
C.	Planning Level Cost Estimates.....	31
10.	Recommendations.....	31
11.	References.....	32
Appendix A: 30% Design Examples for Edgewood Road, Madbury Road, mill Pond Road.....		33
Appendix B: Pollutant Load and Costing Methodology.....		34

Table of Tables

Table 1: Mill Pond Study Area Characteristics	11
Table 2 - Priority Implementation Schedule for BMPs from LO Analysis	20
Table 3 - BMP Menu for Managing 257 acres and Achieving 2,400 lbs of N Reduction	21
Table 4 - Cost Options for EIC Reduction Implementation Schedules Ranging from 15-25 Yrs 23	
Table 5 - Pollutant Load Analysis Results for Example BMPs on Edgewood Road (EW1), Madbury Road (MR1), and Mill Pond Road (MP1).....	27
Table 6: BMP Pollutant Removal and Cost Estimates for a 1/4" Water Quality Volume	31

Table of Figures

Figure 1 - Mill Pond Watershed Overview	7
Figure 2: Study Area Subwatersheds	8
Figure 3 - Mill Pond Watershed Soils and Land Cover	9
Figure 4 - Mill Pond Watershed Land Use	10
Figure 5 – Impervious Cover Percentage versus Area for Mill Pond Total, Subwatershed 1 and 2	12
Figure 6 – Nitrogen Loading by Subwatershed S1 for Lower Mill Pond Watershed.....	14
Figure 7 – Heat Map of Nitrogen Loading by Subwatershed S1 and Potential Retrofit Opportunities for Lower Mill Pond Watershed	15
Figure 8 –Nitrogen Loading by Subwatershed 2 for Mill Pond Watershed	16
Figure 9 – BMP-Scale Optimization Example for Commercial Bioretention with Annual Exported Load and Volume based on Water Quality Volume (Aka Capture Depth)	18
Figure 10 – Residential Land Use-Scale BMP Optimization Example	19
Figure 11 – Estimated BMP Cost by Linear Optimization by Drainage Area and Nitrogen Reduction	21
Figure 12 - Stormwater Tree Planter Combined with Catch Basin	24
Figure 13: Parking Lot Bioretention	24
Figure 14: Streetscape with Street Trees Adaptable for Stormwater Management.....	25
Figure 15: Subsurface Infiltration with Stone Reservoir and Isolator Row Pretreatment Chamber	25
Figure 16 – Edgewood Road BMP 'EW1' Detailed Location and Drainage Area	28
Figure 17 – Madbury Road BMP 'MR1' Detailed Location and Drainage Area	29
Figure 18 – Mill Pond Road BMP 'MP1' Detailed Location and Drainage Area	30

<u>Acronym</u>	<u>Definition</u>
ASCE	AMERICAN SOCIETY OF CIVIL ENGINEERS
BMP	STORMWATER BEST MANAGEMENT PRACTICE
CWA	CLEAN WATER ACT
DWRE	DIPLOMATE, WATER RESOURCES ENGINEER
EIC	EFFECTIVE IMPERVIOUS COVER
EPA	UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
EWRI	ENVIRONMENTAL WATER RESEARCH INSTITUTE
EMC	EVENT MEAN CONCENTRATION
FCA	FINANCIAL CAPABILITY ANALYSES
FR	FEDERAL REGISTER
GIS	GEOGRAPHIC INFORMATION SYSTEMS
HRU	HYDROLOGIC RESPONSE UNIT
IA	IMPERVIOUS AREA
ICM	IMPERVIOUS COVER MODEL
LA	LOAD ALLOCATION
LID	LOW IMPACT DEVELOPMENT
LIDAR	LIGHT DETECTION AND RANGING
MSGP	MULTI-SECTOR GENERAL PERMIT
NCDC	NATIONAL CLIMATE DATA CENTER
NCP	NITROGEN CONTROL PLAN
NOI	NOTICE OF INTENT
NRCC	NORTHEAST REGIONAL CLIMATE CENTER
NRCS	NATURAL RESOURCES CONSERVATION SERVICE
NPDES	NATIONAL POLLUTION DISCHARGE ELIMINATION PERMITS
NPS	NONPOINT SOURCE POLLUTION
PE	PROFESSIONAL ENGINEER
PLA	POLLUTANT LOADING ANALYSES
PLER	POLLUTANT LOAD EXPORT RATES
SWM	STORMWATER MANAGEMENT
SWMM	STORMWATER MANAGEMENT MODEL
SWPPP	STORMWATER POLLUTION PREVENTION PLAN
TMDL	TOTAL MAXIMUM DAILY LOAD
TN	TOTAL NITROGEN
TSS	TOTAL SUSPENDED SOLIDS
USDA	UNITED STATES DEPARTMENT OF AGRICULTURE
USGS	UNITED STATES GEOLOGICAL SURVEY
UWRCC	URBAN WATER RESOURCES RESEARCH COUNCIL
WLA	WASTE LOAD ALLOCATION
WQV	WATER QUALITY VOLUME

1. SUMMARY

The goal of the Mill Pond Nutrient Control study was to identify restorative actions that will be effective within the life expectancy of the dam and at the same time help address declining water quality in Mill Pond and NPDES permitting requirements. Aspects of this study are intended to be consistent (in part) with the 2017 MS4 permit. This includes source identification reporting, BMPs to be optimized for pollutant removal¹, retrofit inventory and priority ranking. The project included the following elements:

Watershed Assessment: A watershed assessment was conducted using existing GIS data layers including: LiDAR contour topographic data, land use/land cover, impervious surfaces, NRCS soil survey, roads, and infrastructure such as water, sewer, outfalls, catch basins, manholes, parcel boundaries. Nitrogen loads and target reductions were calculated for sources delivered to Mill Pond via stormwater and other non-point sources using approaches approved by EPA.

Nutrient Control Measures: A menu of lowest cost alternative of nitrogen control strategies was developed for non-point source reduction. Specifically, a list of potential nutrient control measures was developed through BMP optimization including non-point source loads from each subwatershed to identify target areas. This includes specific BMP type, BMP size, land use type, soil type, and total areas needed for management. Subcatchments were delineated and potential locations for nitrogen control strategies were identified including load reduction potential.

Implementation Plan and Schedule: A summary level implementation plan was developed for Mill Pond that identified target load reductions, estimated cost, future actions, and next steps. This includes planning level cost estimates for both capital cost and operations and maintenance to support the possibility for future SRF or other grant or loan financing. A range of draft implementation schedules were developed based on ranges from 15-25-year periods of implementation. These ranges included estimated annual costs and annual acreage required for effective impervious cover reduction. Guidance was provided for developing EPA approved implementation schedules. The plan describes measures and nitrogen load reduction estimates from implementation of nitrogen control strategies, for specific land uses and sources, down to the subwatershed level. The breakdown of sources and estimated potential load reductions at the subwatershed level will satisfy some MS4 requirements and will assist prioritization relative to other permitting needs.

Design Examples: 30% design examples were developed for 3 locations: Edgewood Road, Madbury Road, and Mill Pond Road. Design examples included BMP sizing based on the optimization results, BMP selection, pretreatment, and costing for total and unit cost.

¹ Appendix H. Part I, 1.a Additional or Enhanced BMPs.i.2

2. MILL POND BACKGROUND AND REGIONAL CONTEXT

Like many coastal regions, population growth and development in Durham has contributed to an increase in impervious cover and has led to increased pollutant loads and stormwater runoff. As more impervious surface is added, flooding risks are elevated, and water quality is impacted. This has been especially evident in impacts to Mill Pond and the Mill Pond Dam with advancing eutrophication and historically high flood flows. Recent documented changes in climate have resulted in higher-intensity precipitation events, increased rainfall depth, and greater variations in storm duration and frequency which increase these risks and impacts.

Mill Pond is located on the Oyster River and is formed by a manmade dam, separating the river from the tidal zone. The entire Oyster River watershed encompasses roughly 13,700 acres (shown in Figure 1), roughly 4.6% of which is impervious. This study focused on a small portion of the watershed which contains the majority of the urban area that drains to Mill Pond.

In 2009, NHDES concluded that many sub-estuaries in the Great Bay Estuary were impaired by nitrogen, and the Great Bay was placed on the Clean Water Act (CWA) Sec. 303(d) list of impaired and threatened waters (NHDES, 2009). New and revised discharge permits in the watershed are now subject to additional nitrogen requirements including the National Pollutant Discharge Elimination System (NPDES) permits for wastewater treatment facilities, and Municipal Separate Storm Sewer Discharge (MS4) permits for stormwater.

The Town of Durham has been actively engaged in stormwater management and responsibilities for MS4 Phase II Stormwater regulations and nutrient management for the Great Bay. The town also participates in the Great Bay Pollution Tracking and Accounting Pilot Project (PTAPP), a collaborative effort between local communities in our region, regional planning commissions NHDES, and EPA, to enable regional coordination on nitrogen tracking and accounting for the Great Bay region.

A. Environmental Impacts from Growth

Monitoring and research conducted by various university, local, state and federal programs and projects have documented stresses in the Great Bay system. Prominent drivers of change include watershed modification and development resulting in increased impervious cover; increased nutrient and pollutant loading from a rapidly growing coastal population; and ecosystem instability and loss of diversity caused by invasive species, habitat destruction, disease, and others. Each stress drives additional physical, chemical, and biological pressures on the Great Bay system that effect the environmental, lifestyle, and economic benefits valued by local communities. Environmental indicators used by the Piscataqua Regions Estuaries Partnership to identify and track ecosystem health clearly illustrate an ecosystem in trouble. In the most recent State of Our Estuaries 2018 report (PREP, 2018), 14 of 24 indicators showed a declining or cautionary condition. Impervious cover, an indicator of development, shows a long-term increasing trend which is related to condition indicators including nutrient concentration, eelgrass, dissolved oxygen, and macroalgae that show either no improvement or continued quality decline.

B. 2017 NH Small MS4 Permit

Under the MS4 program, towns with urbanized areas as defined by the US Census are required to obtain permit coverage for their stormwater discharges. Durham is subject to the requirements of EPA's 2017 NH Small MS4 General Permit for stormwater discharges. EPA released a final permit in 2017 which contained new provisions for the 6 Minimum Measures (MM):

- 1) Public Education and Outreach
- 2) Public Participation/Involvement
- 3) Illicit Discharge Detection and Elimination
- 4) Construction Site Runoff Control
- 5) Post-Construction Runoff Control
- 6) Pollution Prevention/Good Housekeeping

The new 2017 permit includes new requirements to develop Nitrogen Source Identification Reports² for discharge to impaired water bodies. The reports will assess all significant discharges to determine if they could contribute to the waterbody impairment and identify BMPs and a schedule for implementation to address the impairments.

Aspects of this study for Nutrient Control Measures for Mill Pond are intended to be consistent (in part) with the 2017 MS4 permit. This includes source identification reporting, BMPs to be optimized for pollutant removal³, retrofit inventory and priority ranking.

C. EPA Integrated Planning Framework and Watershed Based Planning

The town and UNH continue to discuss and further develop the comprehensive integrated watershed management plan for the Oyster River Watershed. This includes evaluating wastewater and stormwater funding strategies, and an analysis of nitrogen loading by the WWTP and other sources in the Oyster River Watershed. The June 2012 EPA memorandum, "Integrated Municipal Stormwater and Wastewater Planning Approach Framework" provides guidance for EPA, States and local governments to develop and implement effective integrated plans that satisfy the CWA. The framework outlines the overarching principles and essential elements of a successful integrated plan which includes:

- Maintaining existing regulatory standards that protect public health and water quality.
- Allowing a municipality to balance CWA requirements in a manner that addresses the most pressing public health and environmental protection issues first.
- The responsibility to develop an integrated plan rests on the municipality that chooses to pursue the approach. EPA and/or the State will determine appropriate actions, which may include developing requirements and schedules in enforceable documents.

² 2017 NH Small MS4 General Permit: Appendix H, Requirements Related to Discharges to Certain Water Quality Limited Waterbodies, I. Discharges to water quality limited waterbodies and their tributaries where nitrogen is the cause of the impairment, Part I, 1.b Nitrogen Source Identification Report

³ Appendix H, Part I, 1.a Additional or Enhanced BMPs.i.2

- Innovative technologies, including green infrastructure, are important tools that can generate many benefits, and may be fundamental aspects of municipalities' plans for integrated solutions.

D. 2014 Mill Pond Assessment⁴

Mill Pond has become increasingly impacted by high nutrient concentrations, leading to eutrophication and other water-quality related issues. A number of recent studies have characterized the nutrient-related concerns in water bodies within the Oyster River watershed. A 2014 assessment focused on ponds in the vicinity of Durham, NH and included an assessment of Mill Pond in particular. The key findings of this study are summarized below.

Phosphorus is the primary limiting nutrient in most northern temperate lakes, hence algal growth is typically directly related to phosphorus concentrations. Total phosphorus concentrations in Mill Pond are high, ranging from 0.046 to 0.074 mg/l. Typically in New England lakes, phosphorus concentrations in excess of 0.020 mg/l are sufficient to regularly fuel algal blooms. The presence of soluble reactive phosphorus (readily available for plant growth) in relatively high concentrations on all sampling dates further indicates that there is more phosphorus in Mill Pond than the existing algal and plant community can use. Observed concentrations in College Brook (0.041 to 0.198 mg/l) are substantially higher than those observed in the Oyster River upstream of Mill Pond (0.029-0.054 mg/l) particularly after rain. Although flows are lower in College Brook than the Oyster River, reductions in phosphorus inputs to College Brook will be critical in the long term to reducing phosphorus concentrations in Mill Pond.

Nitrogen can also play a role in determining the type of algae present and the amount of algal growth in a water body since some cyanobacteria (blue-green algae) can fix nitrogen from the atmosphere. Similar to phosphorus, nitrogen concentrations in Mill Pond are high, however, the ratio of nitrogen to phosphorus observed in Mill Pond suggests that, at times, nitrogen as a plant nutrient is in shorter supply than phosphorus. At the concentrations currently observed, there is sufficient nitrogen and phosphorus to grow plants and algae in nuisance quantities. The management challenge is to reduce one or both of these nutrients to levels that will ultimately limit the amount of plant and algal growth that can occur in Mill Pond.

A nitrogen to phosphorus ratio of less than 10 generally suggests nitrogen limitation of algae growth while a ratio greater than 16 suggest phosphorus limitation. Between those numbers, either nitrogen or phosphorus availability may limit algal growth. An examination of water quality data collected in 2013 shows a total nitrogen to total phosphorus ratio ranging from 8.0 to 12.5 in Mill Pond. This range of ratios suggests that algal growth in Mill Pond is limited by phosphorus at times and nitrogen at times, making control of both nitrogen and phosphorus important.

It should be noted that concentrations of both phosphorus and nitrogen in Mill Pond are more than sufficient to grow algae and plants and in fact, light or flushing may be the limiting factor

⁴ 2014 DKWRC, Durham Ponds Assessment and Plan. Prepared for VHB
November 30, 2018
Mill Pond Nutrient Control Measures Final Report

for algal growth currently. Because neither light nor flushing can be changed substantially, reduction of nutrients to the point where they limit plant and algal growth is still the most promising management strategy. However, because nutrient concentrations are currently so high, reductions in plant and algal growth may not be seen until substantial reductions in nutrient loading occur.

The overall watershed of Mill Pond consists of a mixture of rural, agricultural, residential and urban land uses. Because of their abundance and relatively high nutrient export coefficients, the developed areas of the watershed tend to yield a large portion of the nutrient load to the ponds. The 2014 study found that nutrient loading from the watershed was overwhelmingly the largest source of phosphorus and nitrogen to Mill Pond, accounting for greater than 99% of the nutrient load. Thus, watershed management is the key to substantial improvements in the pond.

Current TP and TN loading and in-pond concentrations are more than sufficient to fuel algal blooms and encourage the growth of aquatic plants. In order to realize improvement in the appearance of the ponds, target reductions of 66% for phosphorus and 69% for nitrogen were calculated of the 2014 Plan. The study further notes that the best pathway to achieving these reduction targets is through installation of watershed BMPs to limit nutrient loading. While improvement may be seen with lesser reduction and reductions beyond these may result in further improvement in the ponds, these levels were chosen to provide a readily apparent improvement in water quality that might be achievable with very aggressive watershed management.

3. WATERSHED ASSESSMENT

Land use, impervious cover, and nitrogen loads were examined for the Mill Pond watershed. Detailed land use data from the NH Granit Statewide GIS Data Clearinghouse was used to assess impervious cover, watershed delineation, and pollutant loading. This included 2011 LiDAR for the Northeast (2m Resolution, 15cm Vertical Accuracy), and Impervious Surfaces in the Coastal Watershed of NH (High Resolution, 2010). Generalized land use data was fit into categories for which nitrogen pollutant load export rates are available. This information can be used for priority ranking to reduce discharges, and pollutant source identification reporting.

The study area represents the most highly urbanized portions of the Mill Pond watershed and is comprised of 2 distinct subwatersheds, the upper watershed area to the west (S1), and the lower area to the east and directly adjacent to Mill Pond (S2) as displayed in Figure 2. The total study area encompasses 1,208 acres, 21% of which is impervious cover. This area contributes an estimated 4,733 lbs of nitrogen annually. Table 1 details land use and pollutant load for subwatersheds 1 and 2. Figure 3 illustrates the dominant soil types within the watershed. The watershed land use is predominantly forest, residential, commercial, and agricultural as illustrated in Figure 4. The upper watershed, S1, is 1,177 acres and contributes an estimated 4,347 lbs of nitrogen annually. The lower watershed, S2, is 91 acres and contributes an estimated 386 lbs of nitrogen annually.

Figure 5 plots percent impervious cover versus area for Mill Pond watershed as a total, and for subwatersheds 1 and 2. This figure is used to determine the degree of impervious cover treatment to reduce effective impervious cover (EIC). EIC of 9% (10%-1% margin of safety) is the oft

recommended management target shown to be protective of natural watershed function in urban areas.⁵

Impervious cover provides a common index between watershed planners, stormwater engineers, water quality regulators, and stream ecologists⁶. EIC is the area that is hydraulically connected to a receiving water by means of continuous paved surfaces, gutters, drain pipes, or other conventional conveyance and detention structures that do not reduce runoff volume (EPA 2011). Reduction of EIC can be achieved using low impact development (LID) BMPs that use filtration and or infiltration to treat a water quality volume⁷. For the purposes of this study EIC reduction is limited solely to LID treatment and does not refer to impervious cover disconnection such as directing downspouts to pervious areas. That is because the generalized impervious cover model (ICM) from which the 9% EIC is based upon, does not differentiate between the degree of IC connectivity. With this approach it is possible to track the reduction of EIC throughout a watershed as LID BMPs are implemented.

⁵ The impervious cover model (ICM) quantifies stream integrity as a function of watershed impervious cover (Schueler et al. 2009). Numerous studies have identified 10-14% impervious cover as a threshold above which stream impairments become marked (Booth and Jackson 1997; CWP 2003; Deacon et al. 2005; Klein 1979; Schueler 1994; Schueler et al. 2009).

⁶ Arnold and Gibbons 1996; Schueler et al. 2009

⁷ Hlas, V., R. Roseen, et al. (2013). An Examination of the Reduction of Effective Impervious Cover and Ecosystem Watershed Response. Department of Civil Engineering. Durham, NH, University of New Hampshire Stormwater Center.




Figure 1 - Mill Pond Watershed Overview





Figure 2: Study Area Subwatersheds




Figure 3 - Mill Pond Watershed Soils and Land Cover




Figure 4 - Mill Pond Watershed Land Use

Table 1: Mill Pond Study Area Characteristics

Land Use Type	Hydrologic Soil Group	Subwatershed 1		Subwatershed 2		Entire Study Area	
		Area (acres)	Annual Nitrogen Export (lbs)*	Area (acres)	Annual Nitrogen Export (lbs)*	Area (acres)	Annual Nitrogen Export (lbs)*
Agriculture	-	0.5	1.4	0.0	0.0	0.5	1.4
	A	29.3	76.1	0.0	0.0	29.3	76.1
	B	40.0	104.1	0.1	0.1	40.1	104.3
	C	88.8	230.9	10.0	26.1	98.8	257.0
	D	8.2	21.2	0.7	1.8	8.8	23.0
	IMP	11.2	127.0	0.1	0.8	11.3	127.8
All Residential	-	0.0	0.0	0.3	0.6	0.3	0.6
	A	10.8	3.3	0.7	0.2	11.5	3.5
	B	0.4	0.5	1.0	1.2	1.4	1.6
	C	35.3	84.8	8.8	21.1	44.1	105.9
	D	29.3	105.5	16.0	57.5	45.3	163.0
	IMP	35.6	502.4	10.4	147.0	46.1	649.4
Barren	-	0.0	0.0	0.0	0.0	0.0	0.0
	A	0.5	0.2	0.0	0.0	0.5	0.2
	B	0.0	0.0	0.0	0.0	0.0	0.0
	C	5.8	13.8	0.0	0.0	5.8	13.8
	D	0.0	0.0	0.0	0.0	0.0	0.0
	IMP	0.0	0.3	0.0	0.0	0.0	0.3
Commercial	-	0.5	1.3	0.0	0.0	0.5	1.3
	A	7.2	2.2	0.0	0.0	7.2	2.2
	B	0.0	0.0	0.0	0.0	0.0	0.0
	C	12.4	29.9	0.5	1.3	13.0	31.2
	D	28.7	103.4	0.7	2.3	29.4	105.7
	IMP	98.9	1483.4	3.9	59.2	102.8	1542.6
Forest	-	1.7	0.8	0.8	0.4	2.5	1.2
	A	40.3	20.1	1.6	0.8	41.9	20.9
	B	68.3	34.2	5.3	2.7	73.6	36.8
	C	309.3	154.7	5.3	2.7	314.6	157.3
	D	93.8	46.9	11.6	5.8	105.4	52.7
	IMP	6.4	71.8	0.4	4.9	6.8	76.7
Highway/ Freeway	-	0.0	0.0	0.0	0.0	0.0	0.0
	A	0.1	0.0	0.0	0.0	0.1	0.0
	B	0.1	0.2	0.0	0.0	0.1	0.2
	C	12.5	30.0	0.0	0.0	12.5	30.0
	D	2.1	7.4	0.2	0.7	2.3	8.2
	IMP	45.9	481.6	4.6	48.7	50.5	530.3
Industrial	-	0.6	1.5	0.0	0.0	0.6	1.5
	A	1.6	0.5	0.0	0.0	1.6	0.5
	B	1.5	1.7	0.0	0.0	1.5	1.7
	C	5.0	12.0	0.0	0.0	5.0	12.0
	D	3.4	12.2	0.0	0.0	3.4	12.2
	IMP	18.5	276.8	0.0	0.0	18.5	276.8
Open Land	-	0.0	0.0	0.0	0.0	0.0	0.0
	A	1.2	0.4	0.0	0.0	1.2	0.4
	B	0.1	0.1	0.0	0.0	0.1	0.1
	C	25.3	60.6	0.0	0.0	25.3	60.6
	D	2.4	8.7	0.0	0.0	2.4	8.7
	IMP	20.6	233.0	0.0	0.0	20.6	233.1
Water	-	9.2	0.0	6.3	0.0	15.5	0.0
	A	0.1	0.0	0.0	0.0	0.1	0.0
	B	0.0	0.0	0.8	0.0	0.8	0.0
	C	3.8	0.0	0.5	0.0	4.3	0.0
	D	0.0	0.0	0.0	0.0	0.0	0.0
	IMP	0.0	0.0	0.0	0.0	0.0	0.0
Totals		1,117	4,347	91	386	1,208	4,733

*Based on EPA, 2017 PLERS




Figure 5 – Impervious Cover Percentage versus Area for Mill Pond Total, Subwatershed 1 and 2

4. NITROGEN SOURCE IDENTIFICATION REPORTING

This Mill Pond study included elements required in the new 2017 MS4 permit. Specifically this report would address requirements to develop Nitrogen Source Identification Reports⁸ for discharge to impaired water bodies. The reports need to assess all significant discharges to determine if they could contribute to the waterbody impairment and identify BMPs and a schedule for implementation to address the impairments. This report addresses report elements 1, 3, 4, and 5 (partially) which include the following elements:

1. Calculation of total MS4 area draining to the water quality limited water segments or their tributaries, incorporating updated mapping of the MS4 and catchment delineations,
2. All screening and monitoring results targeting the receiving water segment(s)
3. Impervious area and DCIA for the target catchment
4. Identification, delineation and prioritization of potential catchments with high nitrogen loading
5. Identification of potential retrofit opportunities or opportunities for the installation of structural BMPs during redevelopment

It is important to note that the MS4 requirements need to be reviewed for completeness both for source identification reporting and other elements.

Figure 6 examines the lower S1 watershed, the subwatershed delineation, identification of nitrogen load, drainage infrastructure, and potential retrofit opportunities. Figure 7 is a heat map of nitrogen load that illustrates the areas of highest loading concern for prioritization of structural BMPs. Figure 8 illustrates for subwatershed 2 the delineation, identification of nitrogen load, drainage infrastructure, and potential retrofit opportunities in the immediate proximity to Mill Pond.

⁸ 2017 NH Small MS4 General Permit: Appendix H, Requirements Related to Discharges to Certain Water Quality Limited Waterbodies, I. Discharges to water quality limited waterbodies and their tributaries where nitrogen is the cause of the impairment, Part I, 1.b Nitrogen Source Identification Report




Figure 6 – Nitrogen Loading by Subwatershed S1 for Lower Mill Pond Watershed




Figure 7 – Heat Map of Nitrogen Loading by Subwatershed S1 and Potential Retrofit Opportunities for Lower Mill Pond Watershed




Figure 8 –Nitrogen Loading by Subwatershed 2 for Mill Pond Watershed

5. STORMWATER MANAGEMENT AND RETROFIT OPPORTUNITIES

BMPs for stormwater management and nitrogen controls include both structural and non-structural practices to reduce runoff volume from stormwater sources such as impervious surfaces (rooftops and parking lots), residential areas, commercial/industrial/institutional properties, roads, outdoor recreational spaces (i.e., parks), agricultural areas, and managed turf (i.e., golf courses, lawn). Common BMPs for nutrient controls include biofiltration (bioretention, raingardens, tree planters), gravel wetlands, infiltration practices (dry wells, and subsurface infiltration), and porous pavements. A wealth of BMP sources exists in the literature and locally at the UNH Stormwater Center. A list of practices can be found in the New Hampshire Stormwater Manual on the [NHDES website](#).

6. BMP OPTIMIZATION FOR NITROGEN REMOVAL

The 2017 MS4 permit includes the requirement for BMPs to be optimized for pollutant removal⁹. Optimization is especially valuable for retrofitting and redevelopment because it involves sizing of a BMP to achieve the greatest performance for least cost. Results are influenced by pollutant type, soils, land use, BMP performance and cost, and application constraints (i.e. prohibiting certain BMPs for certain land uses). Optimization can occur at multiple scales. In its simplest sense optimization is done at the BMP level for sizing an individual system. At its most complex it can be used at the watershed-scale to determine a menu of lowest cost highest performance BMPs by type and size while factoring in multiple land uses, soils, performance, cost, and constraints.

The Mill Pond optimization study was conducted using a previously developed optimization model¹⁰ developed in collaboration with and approved by EPA, and a related EPA optimization tool¹¹. The model selects the most cost-effective management measures for a range of increasing runoff reduction. The optimization model runs repeatedly, changing the target volume reduction with each iteration. It evaluates the runoff control strategies based upon user defined constraints including available land for implementation, volume reduction capability based on capture depth of the BMP, and cost to implement the strategy. This model was first applied at the system level to develop a series of BMP performance curves. It was next applied at the land use scale to identify the most cost-effective options for each particular land use. For the Mill Pond analysis, the optimization tool was focused on the study area described in previous sections for the range of feasible runoff control measures, and the range of land uses.

⁹ Appendix H. Part I, 1.a Additional or Enhanced BMPs.i.2

¹⁰ Roseen, R., Watts, A., Bourdeau, R., Stacey, P., Sinnott, C., Walker, T., Thompson, D., Roberts, E., and Miller, S. (2015). Water Integration for Squamscott Exeter (WISE), Preliminary Integrated Plan, Final Technical Report. Portsmouth, NH, Geosyntec Consultants, University of New Hampshire, Rockingham Planning Commission, Great Bay National Estuarine Research Reserve, Consensus Building Institute.

¹¹ EPA (2015). Opti-Tool for Stormwater and Nutrient Management. Boston, MA, U.S. Environmental Protection Agency, Region 1, New England Tetra Tech.

A. BMP Optimization Examples at the BMP and Land Use Scale

Example 1 and Figure 9 below illustrates the process of how optimization of the size of a bioretention system can occur based on varying the capture depth of the water quality volume. Example 2 and Figure 10 illustrate how the optimization occurs at a land-use scale.




Figure 9 – BMP-Scale Optimization Example for Commercial Bioretention with Annual Exported Load and Volume based on Water Quality Volume (Aka Capture Depth)

Example 1: BMP optimization for bioretention at 0.25” and 1” water quality volumes

From the BMP performance curve for a high-performance bioretention we can see that for a type A soil, 4 systems designed to treat a 0.25” water quality volume in replace of one system to treat a 1” water quality volume would remove an additional 27 lbs of Nitrogen per year at nearly equivalent costs, or approximately 315% greater optimization. A single system treating a 1” water quality volume for 1 acre will remove approximately 12.7 lbs N/acre/year. Whereas 4 smaller systems across 4 acres designed to treat 0.25” water quality volume per acre will each remove 10 lbs N/acre/year for a total of 40 lbs N per year.

Example 2: BMP optimization for a range of nitrogen control measures for residential land use

Figure 10 is an example of an optimization for a residential land use which shows the cost to achieve reduction in relation to the nitrogen management practices ordered in terms of cost efficiency. This process enables the identification of the

point at which cost effectiveness and pollutant reduction is greatest and the feasibility to implement cost effective and pollutant load reduction management practices begins to decline. In this example, 10,000 pounds of nitrogen can be reduced at a cost of about \$7 million dollars (\$700 per pound N reduced). In contrast, as cost efficiency begins to decline removal of 12,500 pounds costs an estimate \$15 million dollars (\$1,200 per pound N reduced), and 15,000 pounds is at a cost of nearly 44 million dollars (\$2,930 per pound N reduced). This process demonstrates the cost efficiency of low-cost rooftop infiltration and small BMPs sized to capture the first-flush for nitrogen which results in the majority of pollutant mass being washed off from runoff in the beginning of a storm (0.25-0.5" WQV). Additional removal occurs at higher cost in more expensive systems.




Figure 10 – Residential Land Use-Scale BMP Optimization Example

B. BMP Optimization and Effective Impervious Cover Reduction in the Mill Pond Watershed

The power of the optimization analysis lies in its ability to identify the most cost-effective BMP options for achieving a desired nitrogen load reduction based on the land use and land cover characteristics in the Mill Pond watershed. Figure 11 illustrates the treated area and nitrogen reduction by estimated cost as computed within the optimization analysis. For this study the level of reduction required to reduce effective impervious cover (EIC) in the watershed to 9% was used as the recommended target load reduction for the Mill Pond watershed. The analysis indicates that

a target EIC of 9% will require managing runoff from 257 acres of impervious cover and would result in the reduction of 2,400 lb in annual nitrogen load, at an estimated cost of \$1,762,000.

Table 2 shows the recommended order of implementation for each BMP/land use/land cover combination identified in the optimization analysis. Table 3 displays the menu of BMPs developed through optimization to manage 257 acres and achieving 2,400 lbs of N reduction. The table lists the acreage treated and runoff volume managed for each BMP and a planning level cost analysis.

Table 2 - Priority Implementation Schedule for BMPs from LO Analysis

Priority	Land Use	Land Cover	BMP	System Size
1	Commercial	Roof	Dry Well	0.25" WQV
1	Residential	Roof	Dry Well	0.50" WQV
3	Industrial	Roof	Dry Well	0.25" WQV
4	Industrial	Impervious	Gravel Wetland	0.25" WQV
5	Residential	Impervious	Raingarden	0.50" WQV
6	Outdoor	Impervious	Gravel Wetland	0.25" WQV
7	Commercial	Impervious	Gravel Wetland	0.25" WQV
8	Commercial	Impervious	HE Bioretention	0.25" WQV
9	Commercial	Impervious	Subsurface Infiltration	0.25" WQV
10	Road	Impervious	Gravel Wetland	0.25" WQV
11	Road	Impervious	Bioretention	0.25" WQV
12	Commercial	HSG D	Gravel Wetland	0.25" WQV




Figure 11 – Estimated BMP Cost by Linear Optimization by Drainage Area and Nitrogen Reduction

Table 3 - BMP Menu for Managing 257 acres and Achieving 2,400 lbs of N Reduction

Land Use	Land Cover	BMP	System Size	Treatment (lbs N/acre)	Recommended Acreage	Total Available Acreage	% Acreage Utilized	Construction Cost (\$/acre)	Unit Cost (\$/lb N)	Total N Load Reduction (lbs)	Total Cost
Industrial	Impervious	Gravel Wetland	0.25" WQV	10.65	12.0	11.99	100%	5900	\$ 554	127.7	\$ 70,767
Outdoor	Impervious	Gravel Wetland	0.25" WQV	7.66	20.6	20.62	100%	5900	\$ 770	158.0	\$ 121,686
Residential	Roof	Dry Well	0.5" WQV	11.32	18.9	18.88	100%	7000	\$ 618	213.8	\$ 132,182
Residential	Impervious	Raingarden	0.5" WQV	10.21	27.2	27.17	100%	7000	\$ 686	277.4	\$ 190,213
Commercial	Roof	Dry Well	0.25" WQV	13.09	20.6	20.57	100%	4000	\$ 306	269.2	\$ 82,272
Industrial	Roof	Dry Well	0.25" WQV	13.09	6.5	6.46	100%	4000	\$ 306	84.5	\$ 25,834
Road	Impervious	Gravel Wetland	0.25" WQV	8.52	41.9	50.5	83%	5900	\$ 692	357.1	\$ 247,313
Commercial	Impervious	Gravel Wetland	0.25" WQV	10.65	59.2	82.27	72%	5900	\$ 554	630.9	\$ 349,490
Commercial	HSG D	Gravel Wetland	0.25" WQV	3.06	20.5	29.37	70%	5900	\$ 1,928	62.8	\$ 121,050
Commercial	Impervious	HE Bioretention	0.25" WQV	9.21	16.5	82.27	20%	12255	\$ 1,331	151.5	\$ 201,648
Road	Impervious	Bioretention	0.25" WQV	4.79	8.6	50.5	17%	11400	\$ 2,380	41.1	\$ 97,875
Commercial	Impervious	Subsurface Infiltration	0.25" WQV	3.94	6.6	82.27	8%	18500	\$ 4,695	25.9	\$ 121,762
					259					2,400	\$ 1,762,089

7. IMPLEMENTATION SCHEDULE

A. Scheduling and Cost Considerations for Mill Pond

Implementation schedules are a requirement for the new MS4. Typically, a requirement for EPA approval requires using established guidance for scheduling by performing a financial capability analyses (FCA) (EPA 2014). An FCA is conducted to evaluate the impact on residential rate payers using indicators including household income, existing rates and taxes, as well as allowing a flexibility of schedule to be responsive to circumstances unique to a community, while advancing the goal to protect clean water. A final schedule will provide metrics and milestones that must be tracked and accounted for and reported in the Annual Report on the Nitrogen Control Plan (NCP).

One of the critical elements to be considered with an extended implementation schedule is that a multi-5-yr permit cycle period would benefit from private sector redevelopment. It could be expected that as redevelopment occurs that enhanced stormwater management will be required due to revised municipal stormwater regulations. The revised stormwater regulations require management of nitrogen for new and redevelopment including municipal capital improvement projects that impact stormwater management. In many communities up to 50% of the improvements could occur in the private sector. Areas associated with management of NPS (non-point source) for municipally owned and managed land include parks, schools, roads, municipal offices, police and fire, public works facilities, and impervious areas in the urban center typically managed by the municipality. With this approach the total cost of NPS management is covered by the land uses that generate stormwater runoff, both municipal and private sector.

In absence of a financial capability analysis, a range of implementation periods was examined to determine the yearly rate for treated acres and the estimated cost to implement. The cost in this instance is total cost and does not differentiate between private and public sector. Table 4 illustrates implementation schedules ranging from 15 years (3 permit cycles), 17.1 acres per year at an annual cost of \$117,500 to 25 years (5 permit cycles) and 10.3 acres per year at \$70,500 annually.

Table 4 - Cost Options for EIC Reduction Implementation Schedules Ranging from 15-25 Yrs

Implementation Period (yrs)	Yearly Rate of Area Treated- Total (AC/YR)	Yearly Cost to Implement Total
15	17.1	\$117,467
16	16.0	\$110,125
17	15.1	\$103,647
18	14.3	\$97,889
19	13.5	\$92,737
20	12.8	\$88,100
21	12.2	\$83,905
22	11.7	\$80,091
23	11.2	\$76,609
24	10.7	\$73,417
25	10.3	\$70,480

**Assumptions: 257 acres treated for impervious cover reduction to achieve 9% EIC within the watershed; estimated cost to implement \$1,762,000 in 2018 costs; estimated yearly cost to implement is average over period of time, it would be expected that early "low hanging fruit" installations would be less costly, and later installations more expensive.*

B. Guidance for Developing Implementation Schedules

Implementation scheduling approaches include guidance for CSO management, Integrated Planning, and MS4 implementation.

- Wastewater scheduling typically follows the FCA analysis. “Combined Sewer Overflows: Guidance for Financial Capability Assessment and Schedule Development” (FCA Guidance) (EPA 832-B-97-004)
- Integrated planning is using similar info FCA Framework 2014. Financial Capability Assessment Framework for Municipal Clean Water Act Requirements (EPA, 2014)
- MS4 implementation for NH currently does not indicate a specific implementation schedule. No minimum period for an implementation schedule for Post Construction Stormwater Management (Minimum Measure 5) is required. We have heard from EPA in the public forum that an extended period of time will be allowable.
- Similarly, EPA Headquarters, and Region 1 Leadership spoke at the September 2013 NACWA Integrated Planning Workshop in Portsmouth, NH, that extended implementation periods similar to CSO implementation are conceivable in the range of 4 or more permit cycle period.

8. BMP EXAMPLES FOR NUTRIENT CONTROL IN URBAN AREAS

There are several best management practices that can be used in the municipal, commercial, industrial, and residential areas to manage runoff from roof tops, impervious surfaces and pervious surfaces. This includes dry wells, subsurface infiltration, gravel wetlands, porous pavements, biofiltration, and high efficiency bioretention.

Figure 12 illustrates a tree planter installed as part of a road reconstruction and sewer improvements. The tree planter combines a tree well and catchbasin with an engineered soil that provides a growing medium and water quality filter. The planter was designed for considerations of low maintenance and winter maintenance in that it can be cleared easily by snow plow and sediment and debris removal is limited to a deep sump and cleaning by vactor truck. With the tree planter grate the sidewalk area is usable for pedestrian travel. Tree planters, bioretention, and other forms of infiltration or biofiltration can be combined with streetscapes for added functionality.



Figure 12 - Stormwater Tree Planter Combined with Catch Basin

Figure 13 shows a bioswale with pretreatment systems located in a parking lot that could be applied in a road right-of-way. Figure 14 is an example of a streetscape and tree planter that could easily be combined for stormwater management. The streetscape has a combination of pedestrian considerations, areas for local business to use the sidewalks, and park benches, all of which could allow for use of some type of planter or infiltration below ground. Figure 15 shows large scale subsurface infiltration combined with an isolator row for pretreatment. The isolator row is a wrapped chamber that prevents clogging of the stone bed. A subsurface infiltration system such as this combined with a pretreatment design could be used effectively for flood control and nutrient reduction.



Figure 13: Parking Lot Bioretention



Figure 14: Streetscape with Street Trees Adaptable for Stormwater Management



Figure 15: Subsurface Infiltration with Stone Reservoir and Isolator Row Pretreatment Chamber

9. BMP IMPLEMENTATION EXAMPLES FOR MILL POND

A. Design and Maintenance

Three BMPs examples were developed for various locations within Durham (See Appendix A). BMPs were each designed to a 30% level in order to demonstrate BMP sizing considering land use, soils, and calculating the nitrogen-reduction potential and cost for systems of this type. These BMPs are all relatively simple installations which make use of existing drainage infrastructure for overflow and bypass and as such no additional piping (beyond the BMPs) is proposed.

Roadside bioswales with pretreatment were designed for Edgewood Road (EW1) and Madbury Road (MR1) designed to manage the ¼” WQV from a road and residential neighborhood (Figure 16 and Figure 17). A third system on Mill Pond Road (MP1) with a combination of pretreatment and subsurface infiltration was designed to manage the ¼” WQV from road, residential, and commercial areas (Figure 18). A pollutant loading analysis was performed for each BMP to determine the associated nitrogen load reduction potential.

All BMPs were designed for low maintenance with an emphasis on pretreatment to reduce maintenance needs. The maintenance goal is to use existing staff and equipment for standard catch basin cleaning. The focus on pretreatment should provide easy-to-maintain shallow sumps for collection of sediment and trash with standard maintenance procedures using vector trucks and requires no specialty equipment or training. The absence of a pre-filter may allow trash and debris to prematurely clog the biofilter media or infiltration bed. Trash and debris can require frequent maintenance for aesthetics in high loading land uses and reduce the infiltration rate of filtration media.

To ensure the effectiveness of BMPs, regular inspections and maintenance is necessary. Generally, inspection and maintenance falls into two categories: expected routine maintenance and non-routine (repair) maintenance. Routine maintenance is performed regularly to maintain both aesthetics and their good working order. Routine inspection and maintenance helps prevent potential nuisances (odors, mosquitoes, weeds, etc.), reduces the need for repair maintenance, and insures long term performance.

Under MS4 rules, owners and operators are responsible for implementing BMP inspection and maintenance programs and having penalties in place to deter infractions. The rules recommend that all stormwater BMPs should be inspected on a regular basis for continued effectiveness and structural integrity.

B. Pollutant Load Reduction


For each location and proposed BMP a pollutant loading analysis was performed in order to quantify the potential to reduce total nitrogen loading to Mill Pond. Nitrogen removal performance was based on values derived as part of the EPA, 2017 revision to the NH MS4 General Permit, using pollutant load export rates (PLERs), BMP types, drainage areas, land uses, and soil types. Results were compiled for BMPs sized to accommodate the ¼” water quality volume and are presented in Table 5.

Table 5 - Pollutant Load Analysis Results for Example BMPs on Edgewood Road (EW1), Madbury Road (MR1), and Mill Pond Road (MP1)

BMP ID	Soil Type at BMP	% Impervious Cover	Drainage Area (acres)	Annual TN Load (lbs)	Volume (ft3)	TN Captured (lbs)
EW1	A	37%	0.71	3.7	245	1.9
MR1	D	51%	1.58	13.4	730	6.9
MP1	C	57%	5.43	49.8	2,790	25.1
			7.73	66.9	3,766	33.9



Figure 16 – Edgewood Road BMP 'EW1' Detailed Location and Drainage Area



- MR1 Drainage Area
- Flow Accumulation Lines (LiDAR-Derived)
- Proposed BMP Location

Data Sources:
 -DEM: 2011 LiDAR for the Northeast, NH GRANIT
 -Land Use Types: NH GRANIT, 2015
 -Basemap: Google Earth Imagery, 10/5/16

Figure 17 – Madbury Road BMP 'MR1' Detailed Location and Drainage Area



Figure 18 – Mill Pond Road BMP 'MP1' Detailed Location and Drainage Area

C. Planning Level Cost Estimates

30% design costing analysis were developed to quantify the total and unit costs (cost per pound of nitrogen removed) for the three example BMPs.

The planning-level cost estimates are based on scalable unit costs developed in prior studies¹⁰ study and the drainage area characteristics for each BMP. Results were compiled for the ¼” water quality volume and are presented in Table 6. Cost estimates presented in this report are conservative and should be further evaluated as designs are finalized and when system size and material quantities are known. Tremendous cost saving opportunities exist when BMP retrofits are phased with road and utility improvements. For example, a bioretention system designed to treat 1 acre of runoff might cost an estimated \$40,000. However, when paired with road improvements the costs may be reduced to \$10,000 due to the shared costs of curbs, sidewalks, and roads.

Table 6: BMP Pollutant Removal and Cost Estimates for a 1/4" Water Quality Volume

BMP #	Capture Volume (ft ³)	TN Capture (lbs)	Total Cost (\$)	Unit Cost (\$/lb)
MP1	3,100	25	\$100,500	\$4,000
EW1	130	2	\$13,200	\$7,000
MR1	525	7	\$29,200	\$4,200

10. RECOMMENDATIONS

As part of future efforts, we recommend the following:

1. Further study to complete the Nitrogen Source Identification Reports for the remaining subwatersheds
2. Advancing BMP designs to 95% level such that they can be included in future capital improvement projects, SRF, and grant funded efforts.
3. Including a study and cost prioritization of non-structural BMPs such as street sweeping, leaf litter control, impervious surface disconnection, urban tree planting, urban fertilizer control, impervious cover removal, soil augmentation, and catch basin cleaning.

Implementation of the recommendations will help Durham address requirements of EPA’s 2017 NH Small MS4 General Permit for stormwater discharges. In particular new requirements to develop a Nitrogen Source Identification Report; and new development and redevelopment stormwater management BMPs be optimized for nitrogen removal; retrofit inventory and priority ranking to reduce nitrogen discharges.

11. REFERENCES

- Booth, D. B., and Jackson, C. R. (1997). "Urbanization Of Aquatic Systems: Degradation Thresholds, Stormwater Detection, And The Limits Of Mitigation." *JAWRA Journal of the American Water Resources Association*, 33(5), 1077-1090.
- CWP. (2003). "Impacts of Impervious Cover on Aquatic Systems." Center for Watershed Protection, Ellicott City.
- Deacon, J. R., Soule, S. A., Smith, T. E., Geological Survey (U.S.), and New Hampshire. Dept. of Environmental Services. (2005). "Effects of urbanization on stream quality at selected sites in the seacoast region in New Hampshire, 2001-03." U.S. Dept. of the Interior, U.S. Geological Survey, Reston, Va.
- EPA (2015). Opti-Tool for Stormwater and Nutrient Management. Boston, MA, U.S. Environmental Protection Agency, Region 1, New England Tetra Tech.
- Hlas, V., R. Roseen, et al. (2013). An Examination of the Reduction of Effective Impervious Cover and Ecosystem Watershed Response. Department of Civil Engineering. Durham, NH, University of New Hampshire Stormwater Center.
- Klein, R. D. (1979). "URBANIZATION AND STREAM QUALITY IMPAIRMENT." *JAWRA Journal of the American Water Resources Association*, 15(4), 948-963.
- Schueler, T. R. (1994). "The Importance of Imperviousness." *Watershed Protection Techniques*, 1(3).
- Schueler, T. R., Fraley-McNeal, L., and Cappiella, K. (2009). "Is Impervious Cover Still Important? Review of Recent Research." *Journal of Hydrologic Engineering*, 14(4), 309-315.
- VHB. 2014. Oyster River Integrated Management Plan for Nitrogen Control. Prepared for Town of Durham, NH
- DK WRC. 2014. Durham Ponds Assessment and Plan. Prepared for VHB.
- Roseen, R., Watts, A., Bourdeau, R., Stacey, P., Sinnott, C., Walker, T., Thompson, D., Roberts, E., and Miller, S. (2015). Water Integration for Squamscott Exeter (WISE), Preliminary Integrated Plan, Final Technical Report. Portsmouth, NH, Geosyntec Consultants, University of New Hampshire, Rockingham Planning Commission, Great Bay National Estuarine Research Reserve, Consensus Building Institute.

**APPENDIX A: 30% DESIGN EXAMPLES FOR EDGEWOOD ROAD, MADBURY ROAD,
MILL POND ROAD**

30% BMP EXAMPLE DESIGNS FOR MILL POND NUTRIENT CONTROL MEASURES

FOR THE DURHAM, NH MILL POND STUDY

PREPARED FOR
TOWN OF DURHAM, NEW HAMPSHIRE




OWNER:
TOWN OF DURHAM
TODD I. SELIG
TOWN ADMINISTRATOR
APRIL TALON
TOWN ENGINEER
8 NEWMARKET ROAD
DURHAM, NH 03824

PREPARED BY:
ROBERT ROSEEN, PE, PHD, D.WRE
JAKE SAHL, MS
WATERSTONE ENGINEERING
STRATHAM, NH 03885

PROJECT MANAGER:
JEFFREY C. PROVOST, P.E.
WESTON & SAMPSON
PORTSMOUTH, NH 03801

DIG SAFE:
CONTACT DIG SAFE AT 811
HOURS PRIOR TO ANY CONSTRUCTION.



LOCATION MAP
NOT TO SCALE



NOTES: UNDERGROUND FACILITIES, STRUCTURES, AND UTILITIES HAVE BEEN PLOTTED FROM AVAILABLE SURVEYS AND RECORDS, AND THEREFORE THEIR LOCATIONS MUST BE CONSIDERED APPROXIMATE ONLY. THERE MAY BE OTHERS, THE EXISTENCE OF WHICH IS PRESENTLY NOT KNOWN. ANYONE USING UTILITY INFORMATION AND DATA PROVIDED HEREIN SHALL CALL DIG SAFE AT 811 SEVENTY TWO (72) HOURS, 3 BUSINESS DAYS IN ADVANCE TO VERIFY THE LOCATION OF UTILITIES PRIOR TO START OF CONSTRUCTION.

This Drawing shall not be used for Construction unless Signed and Sealed For Construction.

NO	DATE	DESCRIPTION	CKD
1	11/7/18	30% DESIGNS	RR



9 GRETA'S WAY
STRATHAM, NH 03885
(p) 603.686.2488

30% BMP EXAMPLE DESIGNS
FOR THE DURHAM, NH MILL POND STUDY
MILL POND
NUTRIENT CONTROL MEASURES

PREPARED FOR:
TOWN OF DURHAM
8 NEWMARKET ROAD
DURHAM, NH 03824

DESIGNED BY: RR
DRAFTED BY: JS
CHECKED BY: RR

COVER SHEET
AND VICINITY
MAPS

JOB #: 171006
SCALE: AS SHOWN
CONTRACT #: N/A
SHEET #: 1



LEGEND - EXISTING

(EXISTING - PHASE 1)

SMH (S)	SEWER MANHOLE	-----	CONTOUR MAJOR
DMH (D)	DRAINAGE MANHOLE	-----	CONTOUR MINOR
(G)	GRADED INLET	--- W --- W ---	WATER LINE
CB (B)	CATCH BASIN	--- G ---	GAS MAIN
CBCL (B)	CATCH BASIN WITH CURB INLET	--- T --- T ---	UNDERGROUND TELEPHONE OR ELECTRIC
TMH (T)	TELEPHONE MANHOLE	--- D --- D ---	STORM DRAINAGE PIPE
(P)	TELEPHONE POLE	--- // --- // --- // ---	OVERHEAD ELECTRIC
(U)	UTILITY POLE	--- o --- o --- o ---	FENCE
(L)	LIGHT POLE	TREE LINE
(S)	SPOT LIGHT	-----	PROPERTY LINE OR RIGHT-OF-WAY
EMH (E)	ELECTRIC MANHOLE	--- VS --- VS ---	SANITARY VACUUM SEWER
(M)	SURVEY MONUMENT	--- S --- S ---	SANITARY GRAVITY SEWER
(X)	PULL BOX	--- FM ---	SANITARY SEWER FORCE MAIN
(W)	WHEELCHAIR RAMP (WCR)	STONE WALL
(O)	BOLLARD	=====	RETAINING WALL
(S)	SIGN	-----	GRANITE CURB
(V)	VERTICAL BENCHMARK	(V)	VALVE PIT TYPE 1 OR TYPE2
(S)	SHRUB	(S)	SINGLE OR DUAL BUFFER TANK
(T)	TREE		
(C)	CURB STOP		
SG (S)	SEWER GATE		
(F)	FIRE HYDRANT		
WMH (W)	WATER MANHOLE		
WS (W)	WATER GATE		

LEGEND - EXISTING

(EXISTING - SURVEYED AREAS)

-----	ABUTTERS LINE (PER TOWN OF EXETER GIS)	(T)	TREE STUMP
-----	STOCKADE FENCE	(C)	CONIFEROUS TREE
-----	PICKET FENCE	(D)	DECIDUOUS TREE
-----	POST & RAIL FENCE	(S)	CONIFEROUS SHRUB
-----	CHAIN LINK FENCE	(B)	DECIDUOUS BUSH
-----	OVERHEAD WIRES	(B)	BORING
---	SEWER LINE	(M)	PEDESTRIAN MAT
---	DRAIN LINE	(C)	CONCRETE
---	GAS LINE	(L)	LANDSCAPED AREA
---	WATER LINE	(S)	CRUSHED STONE
---	MAJOR CONTOUR LINE	(B)	BRICK
---	MINOR CONTOUR LINE	(TYP.)	TYPICAL EDGE OF PAVEMENT
.....	TREE LINE	(S)	SINGLE WHITE LINE
.....	SHRUB LINE	(Y)	SINGLE YELLOW LINE
.....	UTILITY POLE	(D)	DOUBLE YELLOW LINE
.....	UTILITY POLE & GUY WIRE	(C)	CONCRETE
.....	SIGN	(V)	VERTICAL GRANITE CURB
.....	GRANITE BOUND FOUND	(S)	SLOPED GRANITE CURB
.....	IRON PIPE/ROD FOUND	(C)	CONCRETE CURB
.....	POST	(B)	BITUMINOUS BERM
.....	FIRE HYDRANT	(M)	TAX MAP & LOT NUMBER
.....	WATER GATE VALVE		
.....	WATER SHUTOFF VALVE		
.....	GAS GATE VALVE		
.....	GAS SHUTOFF VALVE		
.....	GAS METER		
.....	MAIL BOX		
.....	CATCH BASIN (ROUND)		
.....	CATCH BASIN		
.....	DRAIN MANHOLE		
.....	MANHOLE		
.....	ELECTRIC MANHOLE		
.....	TELEPHONE MANHOLE		
.....	WATER MANHOLE		
.....	SEWER MANHOLE		
.....	BOULDER		

MATERIAL LEGEND

(Pattern)	INFILTRATION CHAMBER
(Pattern)	BRICK SIDEWALK WITH PATTERN TO MATCH EXISTING
(Pattern)	CONCRETE SIDEWALK
(Pattern)	CONCRETE PAVING
(Pattern)	GRASS
(Pattern)	STANDARD "HMA" PAVEMENT
(Pattern)	BIORETENTION SWALE
(Pattern)	TREE PLANTER
(Pattern)	ROW - INFILTRATION GRASSED
(Pattern)	ROW INFILTRATION - TREE TRENCH

DRAWING LIST

SHEET #	DRG No.	DRAWING TITLE
		GENERAL
1	171006-G1	COVERSHEET , VICINITY AND LOCATION MAPS
2	171006-G2	LEGENDS, NOTES AND DRAWING INDEX
3	171006-G3	ABBREVIATIONS AND LEGENDS
		CIVIL
4	171006-C1	EXISTING CONDITIONS PLAN WITH PROPOSED - EW1
5	171006-C2	EXISTING CONDITIONS PLAN WITH PROPOSED - MR1
6	171006-C3	EXISTING CONDITIONS PLAN WITH PROPOSED - MP1
		DETAILS
7	171006-D1	BIORETENTION BMP EW1 AND DETAILS
8	171006-D2	BIORETENTION BMP MR1 AND DETAILS
9	171006-D3	SUBSURFACE INFILTRATION BMP MP1 AND DETAILS
10	171006-D4	PRETREATMENT DETAILS

LEGEND - PROPOSED

(ALL PHASES)

1+00	ROADWAY BASELINE
(+)	EDGE OF POROUS PAVEMENT
(---)	GRANITE CURBING
(---)	CAPE COD BERM
(---)	LIMIT OF STONE RESERVOIR TRENCH
(---)	EDGE TRANSITION DETAIL
(S)	REMOVE AND RESET PARKING METER
(D)	REMOVE AND RESET PARKING METER
(D)	HDPE DRAIN PIPE
(K)	HDPE CAP
(■)	CATCH BASIN
(■)	CATCH BASIN WITH TIP DOWN DETAIL
(●)	DRAIN MANHOLE

UTILITY OPERATING AUTHORITIES	
DRAIN/SEWER/WATER	TOWN OF DURHAM
TELEPHONE	
ELECTRIC	

DRAINAGE NOTES:

- ALL DRAINAGE PIPING SHALL BE 12" INSIDE DIAMETER CORRUGATED HDPE TYPE N-12 PIPE MANUFACTURED BY ADS OR EQUAL SUITABLE FOR H-20 LOADING AT MINIMUM BURIED DEPTH OF 24" UNLESS OTHERWISE NOTED. PIPE SHALL BE SUPPLIED IN 20 FT LENGTHS. JOINTS SHALL BE SOIL TIGHT PUSH ON JOINTS.
- FINAL LOCATION OF ALL DRAINAGE STRUCTURES TO BE COORDINATED WITH RESIDENT PROJECT REPRESENTATIVE PRIOR TO STARTING WORK.
- PIPE SHALL BE SLOPED AT A MINIMUM OF 1.0% UNLESS OTHERWISE NOTED.
- CONTRACTOR IS RESPONSIBLE FOR VERIFYING ALL UTILITIES PRIOR TO EXCAVATION, INCLUDING UTILITIES NOT MARKED BY DIG-SAFE (811), NOT SHOWN ON THE SURVEY, OR NOT MARKED BY THE TOWN. CONTRACTOR IS RESPONSIBLE FOR ANY AND ALL DAMAGES IF AN UNDERGROUND UTILITY IS DAMAGED DURING THE COURSE OF CONSTRUCTION.
- IN THE EVENT THAT ANY UTILITY, UNDERGROUND OR OVERHEAD, IS DAMAGED DURING CONSTRUCTION, CONTRACTOR SHALL IMMEDIATELY NOTIFY ENGINEER AND THE APPROPRIATE UTILITY COMPANY.
- ALL CONNECTIONS BETWEEN PRECAST CONCRETE SECTIONS SHALL BE SEALED WITH NON-SHRINK GROUT.
- CATCH BASINS, INLETS & INFILTRATION BEDS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE STATE DEPARTMENT OF TRANSPORTATION AND ENVIRONMENTAL SERVICES UNLESS OTHERWISE NOTED.
- ALL PRECAST CONCRETE STRUCTURES SHALL BE RATED FOR AASHTO/H-20 LOADING.
- ALL MATERIALS USED AND CONSTRUCTION METHODS EMPLOYED ARE TO BE IN ACCORDANCE WITH THE LATEST FEDERAL, STATE AND TOWN REGULATIONS.
- CONTRACTOR IS RESPONSIBLE FOR DETERMINING DEPTH OF GROUNDWATER AND FOR ALL COSTS ASSOCIATED WITH DEWATERING NECESSARY TO INSTALL STRUCTURES OR PIPING.
- ANY UNSUITABLE MATERIAL ENCOUNTERED DURING EXCAVATION (ORGANICS, PEAT, ETC.) FOR DRAINAGE STRUCTURES SHALL BE DISPOSED OF BY THE CONTRACTOR AT THEIR EXPENSE. CONTRACTOR IS RESPONSIBLE FOR PROVIDING SUITABLE CLEAN BACKFILL FOR BACKFILL AND COMPACTION.
- ALL GATE BOXES, PULL BOXES, CATCH BASIN GRATES AND OTHER UTILITY COVERS SHALL BE RAISED AS NEEDED TO BE FLUSH WITH THE TEMPORARY AND FINAL PAVING IF APPLICABLE.

GENERAL NOTES:

- THIS PROJECT HAS BEEN FINANCED BY A DES COASTAL PROGRAM PLANNING GRANT.
- THE LOCATIONS OF THE BUILDINGS AND PROPERTY LINES WERE TAKEN FROM TOWN SUPPLIED GIS FILES AND SUPPLEMENTED BY THE FIELD SURVEY, REFERENCED BELOW, PERFORMED BY DOUCET LAND SURVEYORS, INC.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR DETERMINING FINAL LOCATION AND DEPTH OF ALL UTILITIES.
- THE CONTRACTOR SHALL CONTACT UTILITY COMPANIES WHEN EXCAVATING IN THE VICINITY OF EXISTING UTILITIES. CONTRACTOR SHALL BE RESPONSIBLE FOR THE REPAIR OF ANY EXISTING UTILITIES DAMAGED DUE TO HIS OPERATION.
- THE CONTRACTOR SHALL STRUCTURALLY SUPPORT AND/OR PROTECT WATER MAIN, GAS, STORM SEWER, SANITARY SEWER OR ANY OTHER EXISTING UTILITIES WHERE NECESSARY IN ACCORDANCE WITH UTILITY OWNER'S REQUIREMENT WHEN EXCAVATING ADJACENT TO OR CROSSING THAT UTILITY.
- CONTRACTOR SHALL NOTIFY ENGINEER IMMEDIATELY OF ANY INTERFERENCE WITH EXISTING UTILITIES AND THE NEW UTILITIES. IF NEW WORK NEEDS TO BE MOVED OR RELOCATED DUE TO A FIELD CHANGE (EXISTING UTILITIES, TREES, OWNER REQUEST, ETC.) COST FOR RELOCATION SHALL BE INCLUDED IN THE INDIVIDUAL BID ITEM BASED ON THE QUANTITY OF ACTUAL MATERIAL INSTALLED.
- CONTRACTOR SHALL BE RESPONSIBLE FOR SUPPORT OF ALL EXCAVATIONS, AS REQUIRED, INCLUDING SHEETING OR BRACING, OR OTHER METHOD APPROVED BY ENGINEER.
- ALL EXISTING ITEMS, INCLUDING BUT NOT LIMITED TO LANDSCAPING, CURBING AND SIDEWALKS DAMAGED BY THE CONTRACTOR SHALL BE RESTORED TO ORIGINAL CONDITIONS AT THE CONTRACTORS EXPENSE.
- WHEN THE CONTRACTOR DISTURBS AN AREA WITHIN 5' OF A UTILITY POLE, THE CONTRACTOR SHALL SUPPORT THAT POLE IN ACCORDANCE WITH UTILITY OWNER'S REQUIREMENTS AT NO ADDITIONAL COST TO THE OWNER.
- LIMIT OF WORK SHALL BE WITHIN THE PUBLIC RIGHT OF WAY OR AS SHOWN ON THE DRAWINGS.
- PROPOSED CONDITIONS SHOWN HEAVY. EXISTING CONDITIONS SHOWN LIGHT.
- ALL PAVEMENT TO BE SAW-CUT.
- NOT ALL OVERHEAD WIRES AND POWER LINES ARE SHOWN ON THE DRAWINGS. THE CONTRACTOR SHALL FIELD VERIFY LOCATIONS BEFORE CONSTRUCTION COMMENCES.
- FOR CLARITY PROFILES DO NOT SHOW UTILITIES.
- PRIOR TO SUBMITTING HIS/HER BID THE CONTRACTOR SHALL VISIT THE SITE TO IDENTIFY AND DOCUMENT WHAT EXISTING CONDITIONS ARE PRESENT ALONG THE STREETSCAPE CORRIDOR AS THESE WILL BE IMPORTANT FOR THE SATISFACTORY COMPLETION OF THE PROJECT.
- NEW SITE GRADES AND ELEVATIONS SHALL BE ESTABLISHED FROM THE ACTUAL EXISTING ELEVATIONS THAT BORDER EACH SECTION OF THE WORK ZONE. THESE ELEVATIONS MAY BE AT STEP BASES, WALK SURFACES, AND EXISTING EARTH AND GARDEN AREAS.
- THE RECONSTRUCTED STREET PAVEMENT SHALL BE GRADED SO THAT SURFACE DRAINAGE PITCHES TO THE NEW DRAINS. INLETS TO BE SET AT A DESIRED GRADE OF 2 PERCENT, WITH A MINIMUM GRADE OF 1 PERCENT. IN SOME AREAS THE SURFACE GRADE OF THE STREET MAY EXCEED 2 PERCENT BUT SHALL NOT EXCEED 3 PERCENT ON A CROSS PITCH ACROSS THE STREET PAVEMENT.
- NEW DRAIN INLETS SHALL HAVE THEIR RIM ELEVATIONS SET TO WORK WITH THE REBUILT STREET GRADES.
- AT ALL TIMES THE CONTRACTOR SHALL MAINTAIN A SMOOTH CURB LINE THAT FUNCTIONS WITH THE SIDEWALK AND STREET GRADES AND IS WITHOUT SHARP BREAKS, HUMMOCKS, AND HOLLOWES. THE FINAL SURFACE OF THE SIDEWALK SHALL HAVE AN EVEN GRADIENT ALONG THE LINE OF THE STREETSCAPE AS WELL AS FROM SIDE TO SIDE AND SHALL FUNCTION WITH A STREET PAVEMENT THAT HAS THE SAME CHARACTER.

This Drawing shall not be used for Construction unless Signed and Sealed For Construction.

NO	DATE	DESCRIPTION	CHKD
1	11/17/18	30% DESIGNS	RR

WATERSTONE ENGINEERING
INNOVATIVE & SUSTAINABLE WATER MANAGEMENT
 9 GRETA'S WAY
 STRATHAM, NH 03865
 (P) 603.686.2488

**30% BMP EXAMPLE DESIGNS
 FOR THE DURHAM, NH MILL POND STUDY
 MILL POND
 NUTRIENT CONTROL MEASURES**

PREPARED FOR:
 TOWN OF DURHAM
 8 NEWMARKET ROAD
 DURHAM, NH 03824

DESIGNED BY: RR
 DRAFTED BY: JS
 CHECKED BY: RR






**LEGENDS,
 NOTES AND
 DRAWING INDEX**

JOB #: 171006
 SCALE: AS SHOWN
 CONTRACT #: N/A
 SHEET #: 2



LIST OF ABBREVIATIONS - PROPOSED

AB ANCHOR BOLT	EA EACH	JT JOINT	REC RECESS/ RECORD
AC ASBESTOS CEMENT	EF EACH FACE	JAN CLO JANITOR'S CLOSET	RECIR RECIRCULATION
ACOJS ACOUSTICAL (SOUND DEADENING)	EJ EXPANSION JOINT		RED REDUCER
ACTL ACOUSTIC TILE	EW EACH WAY	K 1,000 POUNDS (1 KIP)	REF REFERENCE/ REFRIGERATOR
ADDL ADDITIONAL	ECC ECCENTRIC	KC KEENE'S CEMENT	RCP REINFORCED CONCRETE PIPE
ADJ ADJUSTABLE	EFF EFFLUENT	KG KNIFE GATE VALVE	REG REGISTER
AFF ABOVE FINISHED FLOOR	EL or ELEV ELEVATION		REINF REINFORCING
AGGR AGGREGATE	ELB ELBOW	L ANGLE	REM REMOVE
ALLOW ALLOWANCE	ELEC ELECTRIC	LE LEFT END	REP REPAIR
ALT ALTERNATE	ENAM ENAMEL	LF LINEAR FEET	REQD REQUIRED
ALUM ALUMINUM	ENG ENGINE	LL LIVE LOAD	REV REVISE
APPROX APPROXIMATE	ENGR ENGINEER	LLV/ (H) LONG LEG VERT./ (HOR.)	RF ROOF
ARCH ARCHITECT OR ARCHITECTURAL	ENT ENTRANCE	LWL LOW WATER LEVEL	RFG ROOFING
AS AUTOMATED SAMPLER	EQUIP EQUIPMENT	LAM LAMINATE	RL ROOF LEADER
ASB ASBESTOS	EQ or EQUIV EQUAL or EQUIVALENT	LAV LAVATORY	RM ROOM
ASPH ASPHALT	EX, EXIST EXISTING	LT WT LIGHTWEIGHT	RUBB RUBBER
ASSY ASSEMBLY	EXC EXCAVATE	LG LENGTH/ LONG	RES FLR RESILIENT FLOORING
AST ASPHALT TILE	EXH EXHAUST	L PT LOW POINT	
ATPB ASPHALT TREATED PERMEABLE BASE	EXP EXPANSION	LT LIGHT	S SOUTH
	EXT EXTERIOR	LV LOUVER	'S' SUCTION
BCV BUTTERFLY CONTROL VALVE	EXTEND EXTENDED OPERATOR	M MOTOR	SCC SYSTEM CONTROL CENTER
BF BLIND FLANGE	OPER OPER	MCC MOTOR CONTROL CENTER	SF SQUARE FOOT
BIT BITUMINOUS	EXTR EXTRUDE	MGD MILLION GALLONS PER DAY	SJ STEEL JOINT
BL or B BUILDING LINE		MH MANHOLE	SP STOP PLATE
BLDG BUILDING	FA FLANGE ADAPTER	MJ MECHANICAL JOINT	SS STAINLESS STEEL
BLK BLOCK	FC FOOT CANDLE/ FLUSHING CONNECTION	MO MASONRY OPENING	SWD SIDE WATER DEPTH
BM BENCH MARK/ BEAM	FD FLOOR DRAIN/ FIRE DOOR	MAS MASONRY	SADL SADDLE
BO BOARD	FE FIRE EXTINGUISHER	MATL MATERIAL	SCH SCHEDULE
BOF BOTTOM OF FOOTING	FF FAR FACE/ FINISHED FLOOR	MAX MAXIMUM	SECT SECTION
BOT or B BOTTOM	FG FIBERGLASS	MECH MECHANICAL	SEL SELECTION
BP BASE PLATE	FAB FABRICATE	MEMB MEMBRANE	SH SHEET
BRG BEARING	FND FOUNDATION	MTL METAL	SIM SIMILAR
BRK BRICK	FIN FINISH	MEZZ MEZZANINE	SMP SUMP PUMP
BRZ BRONZE	FIN RAD FIN RADIATOR	MFR MANUFACTURER	SOI SPRAYED ON INSULATION
BTW BETWEEN	FITG FITTING	MIN MINIMUM	SPEC SPECIFICATION
BU BUILT UP	FIX FIXTURE	MIR MIRROR	SQ SQUARE
	FL FLASHING/ FLANGE	MISC MISCELLANEOUS	ST STREET
CABN CABINET	FLX CON FLEXIBLE CONTAINMENT TUBE	MMH METHANOL MANHOLE	STAT STATION
CB CATCH BASIN	FLG FLOORING	MTD MOUNTING	STL STEEL
CC CENTER TO CENTER	FLR FLOOR	MULT MULTIPLE	STL JST STEEL JOIST
CEM CEMENT	FLOUR FLOUR		STOR STORAGE
CER CERAMIC	FOC FACE OR COLUMN	N NORTH	STD STANDARD
CF CUBIC FEET	FPRF FIREPROOF	NF NEAR FACE	STIRR STIRRUPS
CFM CUBIC FEET PER MINUTE	FRP FIBERGLASS REINFORCED PLASTIC	NIC NOT IN CONTRACT	STRUC STRUCTURAL or STRUCTURE
CI CAST IRON	FS FOOTING STEP	NPT NATIONAL PIPE THREAD	SUR SURFACE
CIP CAST IRON PIPE	FST FINAL SETTLING TANK	NTS NOT TO SCALE	SUS SUSPENDED/ SUSPENSION
CIRC CIRCLE, CIRCULAR or CIRCUMFERENCE	FT FEET	NUMBER	SYM SYMMETRICAL
CL CENTER LINE	FTG FOOTING	No. or #	SYP SOUTHERN YELLOW PINE
CL2 CHLORINE	FURR FURRING/ FURRED	NOM NOMINAL	SCP STRUCTURAL CLAY PIPE
CL or CLR CLEAR	F&C FRAME AND COVER	NAT NATURAL	SV SOLENOID VALVE
CLG CEILING	F&G FRAME AND GRATING	NS NO SMOKING	
CLKG CAULKING			T TILE, TREAD or TOP
CLF CHAIN LINK FENCE	GC GENERAL CONTRACTOR	OC OVERFLOW STRUCTURE	TDH TOTAL DYNAMIC HEAD
CL JT CONTROL JOINT	GI GALVANIZED IRON	ON CENTER	TIB TOP OF BERM
OMH CHEMICAL MANHOLE	GPM GALLONS PER MINUTE	OD OUTSIDE DIAMETER	TID TOP OF DECK
CMP CORRUGATED METAL PIPE	GV GATE VALVE	OF OUTSIDE FACE	T/FTG TOP OF FOOTING
CMU CONCRETE MASONRY UNIT	GWF GLAZED WALL FINISH	OT OPEN TRUSS	TIG TOP OF GROUT
CS JT CONSTRUCTION JOINT	GA GAUGE	OPNG OPENING	TIGRTG TOP OF GRATING
CO CLEANOUT	GAL GALLON	OPP OPPOSITE	TIMAS TOP OF MASONRY
COL COLUMN, COLOR	GALV GALVANIZED	ORIG ORIGINAL	TIS TOP OF SLAB
COMBN COMBINATION	GEN GENERATOR	OPER OPERABLE	T/STL TOP OF STEEL
CONC CONCRETE	GL GLASS		TW TOP OF WALL
CONN CONNECTION	GR GRADE	P&ID PROCESS INSTRUMENTATION DIAGRAM	THK THICK
CONST CONSTRUCTION	GRAN GRANITE	PCF POUNDS PER CUBIC FOOT	T&B TOP AND BOTTOM
CONT CONTINUOUS	GRTG GRATING	PRV PRESSURE RELIEF VALVE	T&G TONGUE AND GROOVE
CONTR CONTRACTOR	GYP GYPSUM	PSF POUNDS PER SQUARE FOOT	TEL TELEPHONE
COND CONDUIT	GYP BD GYPSUM BOARD	PV PLUG VALVE	TEMP TEMPERATURE
COR CORRIDOR	GMU GLAZED MASONRY UNIT	PSI POUNDS PER SQUARE INCH	TR TOILET ROOM
COORD COORDINATE		POLY, PE POLYETHYLENE	TOL TOLERANCE
CP CONCRETE PLANK	HVAC HEATING and VENTILATION	PAR PARALLEL	TRANS TRANSFORMER
CPLG COUPLING	HD HEAVY DUTY	PARTN PARTITION	TK TANK
CPVC CHLORINATED POLYVINYL CHLORIDE	HDPE HIGH DENSITY POLYETHYLENE	PAT PATTERN	TYP TYPICAL
CRF CHEMICAL RESISTANT FINISH	HDBD HARDBOARD	PAVT PAVEMENT	
CRS COURSE	H EXCH HEAT EXCHANGER	PC PIECE	UNO UNLESS NOTED OTHERWISE
CT CERAMIC TILE	HWL HIGH WATER LEVEL	PDC POWER DISTRIBUTION CENTER	UR URINAL
CTR CONTRACT	HDWR HARDWARE	PERF PERFORATED	UV ULTRAVIOLET
CTRD CENTERED	HGT or HT HEIGHT	PERP PERPENDICULAR	
CTS COPPER TUBE SIZE	HM HOLLOW METAL	PV PINCH VALVE	V VINYL or VERTICAL
CU COPPER	HMA HOT MIX ASPHALT	PLATE/ PROPERTY LINE	VAT VINYL ASBESTOS TILE
CU IN CUBIC INCH	H or HORIZ HORIZONTAL	PLASTER	VT VITRIFIED TILE
CV CHECK VALVE	HP HORSEPOWER	PLAS LAM PLACTIS LAMINATE	VERT VERTICAL
CW COLD WATER/ CIRCULAR WASHER	H PT HIGH POINT	PLBG PLUMBING	VS VACUUM SEWER
CY CUBIC YARD	HTR HEATER	PLE PLANT EFFLUENT	W WATER
	HSC HYDRAULIC SYSTEM CENTER	PLR PILASTER	W/ WITH
DJ DOUBLE JOINT	HYD HYDRANT	PLYWD PLYWOOD	WAS WAS LINE
DL DEAD LOAD		PNL PANEL	WI WROUGHT IRON
DET DETAIL	I IRON	POR PORCELAIN	WG WEIR GATE
DIA, Ø DIAMETER	T INLET	PR PAIR	WL WATER LEVEL
DIAG DIAGONAL	IF INSIDE FACE	PREFAB PREFABRICATED	WO WINDOW OPENING
DEFL DEFLECTION	ID INSIDE DIAMETER	PROP PROPOSED	W/O WITHOUT
DIM DIMENSION	INCL INCINERATOR	PT POINT/ PAINT	WS WATER SURFACE
DIST DISTRIBUTION, DISTANCE	INCL INCLUDE	PVC POLYVINYL CHLORIDE	WWF WELDED WIRE FABRIC
DI DUCTILE IRON	INSUL INSULATION		WC WATER CLOSET
DOZ DOZEN	INT INTERIOR	QT QUARRY TILE	WD WOOD
DN DOWN	INV INVERT	QTY QUANTITY	WP WORKING POINT
DR DOOR	IPS INTERNAL PIPE SIZE		WS WATERSTOP
DWG DRAWING	ISO ISOLATION	R RISER, REACTION, RADIUS	WT WEIGHT
DWL DOWEL	IO INPUT/ OUTPUT	RD ROOF DRAIN/ ROAD	W ST WELDED STEEL PIPE
DH DECK HYDRANT		RO ROUGH OPENING	WV WATER VALVE
DMH DRAINAGE MANHOLE	JCT JUNCTION	ROB RUN OF BANK	WH WALL HYDRANT
	JST JOIST	RAD RADIUS/ RADIATOR	WP WORKING POINT
E EAST		RE RIGHT END	



PROPOSED LEGEND

PROPOSED GRAPHICS; EQUIPMENT, STRUCTURES, ETC., ARE SHOWN AS BOLD LINEWORK AND IN THIS TEXT FORMAT.
 EXISTING GRAPHICS; EQUIPMENT, CONDITIONS, STRUCTURES, ETC. ARE SHOWN AS LIGHT LINEWORK AND IN THIS TEXT FORMAT.

NO	DATE	DESCRIPTION	CKD
1	11/17/18	30% DESIGNS	RR

WATERSTONE ENGINEERING
 INNOVATIVE & CORPORATE WATER MANAGEMENT
 9 GRETA'S WAY
 STRATHAM, NH 03885
 (p) 603.666.2488

30% BMP EXAMPLE DESIGNS
 FOR THE DURHAM, NH MILL POND STUDY
 MILL POND
 NUTRIENT CONTROL MEASURES

PREPARED FOR:
 TOWN OF DURHAM
 8 NEWMARKET ROAD
 DURHAM, NH 03824

DESIGNED BY:	RR
DRAFTED BY:	JS
CHECKED BY:	RR

ABBREVIATIONS AND LEGENDS











JOB #:	171006
SCALE:	AS SHOWN
CONTRACT #:	N/A
SHEET #:	3



This Drawing shall not be used for Construction unless Signed and Sealed For Construction.

BMP ID	SOIL CLASS (NRCS)	SOIL TYPE (NRCS)	HYDROLOGIC SOIL GROUP (NRCS)	HYDRAULIC CONDUCTIVITY (SSNNE)
EW1	GLOUCESTER	VERY STONY FINE SANDY LOAM	A	6.0 IN/HR


MATERIAL LEGEND

-  INFILTRATION CHAMBER
-  BRICK SIDEWALK WITH PATTERN TO MATCH EXISTING
-  CONCRETE SIDEWALK
-  CONCRETE PAVING
-  GRASS
-  STANDARD "HMA" PAVEMENT
-  BIORETENTION SWALE
-  TREE PLANTER
-  ROW - INFILTRATION GRASSED
-  ROW INFILTRATION - TREE TRENCH

LEGEND - EXISTING
(EXISTING - SURVEYED AREAS)

-  BUTTERS LINE (PER TOWN OF EXETER GIS)
-  STOCKADE FENCE
-  PICKET FENCE
-  POST & RAIL FENCE
-  CHAIN LINK FENCE
-  OHW
-  OVERHEAD WIRES
-  SEWER LINE
-  DRAIN LINE
-  GAS LINE
-  WATER LINE
-  MAJOR CONTOUR LINE
-  MINOR CONTOUR LINE
-  TREE LINE
-  SHRUB LINE
-  UTILITY POLE
-  UTILITY POLE & GUY WIRE
-  SIGN
-  GRANITE BOUND FOUND
-  IRON PIPE/ROD FOUND
- POST
- FIRE HYDRANT
- WATER GATE VALVE
- WATER SHUTOFF VALVE
- GAS GATE VALVE
- GAS SHUTOFF VALVE
- GAS METER
- MAIL BOX
- CATCH BASIN (ROUND)
- CATCH BASIN
- DRAIN MANHOLE
- MANHOLE
- ELECTRIC MANHOLE
- TELEPHONE MANHOLE
- WATER MANHOLE
- SEWER MANHOLE
- BOULDER
-  TREE STUMP
-  CONIFEROUS TREE
-  DECIDUOUS TREE
-  CONIFEROUS SHRUB
-  DECIDUOUS BUSH
-  BORING
-  PEDESTRIAN MAT
-  CONCRETE
-  LANDSCAPED AREA
-  CRUSHED STONE
-  BRICK
-  TYP. EDGE OF PAVEMENT
-  SINGLE WHITE LINE
-  SINGLE YELLOW LINE
-  DOUBLE YELLOW LINE
-  CONCRETE
-  VERTICAL GRANITE CURB
-  SLOPED GRANITE CURB
-  CONCRETE CURB
-  BUTUMINOUS BERM
- TAX MAP & LOT NUMBER
- FLOW LINES (ASSUMED)

NOTE:
ALL ELECTRIC, GAS, TEL, WATER, SEWER AND DRAIN SERVICES ARE SHOWN IN SCHEMATIC FASHION. THEIR LOCATIONS ARE NOT
PRECISE OR NECESSARILY ACCURATE. NO WORK WHATSOEVER SHALL BE UNDERTAKEN ON THIS SITE USING THIS PLAN.
LOCATE THE ABOVE SERVICES. CONSULT WITH THE PROPER AUTHORITIES CONCERNED WITH THE SUBJECT SERVICE LOCATIONS
FOR INFORMATION REGARDING SUCH. CALL DIG-SAFE AT 811.



DATA SOURCES:
BACKGROUND: GOOGLE EARTH IMAGERY, 2017
TOPOGRAPHIC DATA: 2011 LIDAR FOR THE NORTHEAST



NO	DATE	DESCRIPTION	CKD
1	11/7/18	30% DESIGNS	RR

WATERSTONE ENGINEERING
INNOVATIVE STORMWATER MANAGEMENT
9 GRETA'S WAY
STRATHAM, NH 03865
(P) 603.686.2488

**30% BMP EXAMPLE DESIGNS
FOR THE DURHAM, NH MILL POND STUDY
MILL POND
NUTRIENT CONTROL MEASURES**

PREPARED FOR:
TOWN OF DURHAM
8 NEWMARKET ROAD
DURHAM, NH 03824

DESIGNED BY: RR
DRAFTED BY: JS
CHECKED BY: RR

EDGEWOOD ROAD BMP - EW1

JOB #: 171006
SCALE: AS SHOWN
CONTRACT #: N/A
SHEET #: 4



This Drawing shall not be used for Construction unless Signed and Sealed For Construction.



BMP ID	SOIL CLASS (NRCS)	SOIL TYPE (NRCS)	HYDROLOGIC SOIL GROUP (NRCS)	HYDRAULIC CONDUCTIVITY (SSSNE)
MR1	HOLLIS-CHARLTON	FINE SANDY LOAMS	A	0.6 IN/HR

NO	DATE	DESCRIPTION	CKD
1	11/7/18	30% DESIGNS	RR



 WATERSTONE ENGINEERING
 INNOVATIVE & FORWARD WATER MANAGEMENT
 9 GRETAS WAY
 STRATHAM, NH 03865
 (P) 603.686.2488

30% BMP EXAMPLE DESIGNS
FOR THE DURHAM, NH MILL POND STUDY
NUTRIENT CONTROL MEASURES

PREPARED FOR:
 TOWN OF DURHAM
 8 NEWMARKET ROAD
 DURHAM, NH 03824
 DESIGNED BY: RR
 DRAFTED BY: JS
 CHECKED BY: RR

MADBURY ROAD
BMP - MR1
 JOB #: 171006
 SCALE: AS SHOWN
 CONTRACT #: N/A
 SHEET #: 5




MATERIAL LEGEND

- INFILTRATION CHAMBER
- BRICK SIDEWALK WITH PATTERN TO MATCH EXISTING
- CONCRETE SIDEWALK
- CONCRETE PAVING
- GRASS
- STANDARD "HMA" PAVEMENT
- BIORETENTION SWALE
- TREE PLANTER
- ROW - INFILTRATION GRASSED
- ROW INFILTRATION - TREE TRENCH

LEGEND - EXISTING
(EXISTING - SURVEYED AREAS)

- ABUTTERS LINE (PER TOWN OF EXETER (IS))
- STOCKADE FENCE
- PICKET FENCE
- POST & RAIL FENCE
- CHAIN LINK FENCE
- OHW
- OVERHEAD WIRES
- SEWER LINE
- DRAIN LINE
- GAS LINE
- WATER LINE
- MAJOR CONTOUR LINE
- MINOR CONTOUR LINE
- TREE LINE
- SHRUB LINE
- UTILITY POLE
- UTILITY POLE & GUY WIRE SIGN
- GRANITE BOUND FOUND
- IRON PIPE/ROD FOUND
- FIRE HYDRANT
- WATER GATE VALVE
- WATER SHUTOFF VALVE
- GAS GATE VALVE
- GAS SHUTOFF VALVE
- GAS METER
- MAIL BOX
- CATCH BASIN (ROUND)
- CATCH BASIN
- DRAIN MANHOLE
- MANHOLE
- ELECTRIC MANHOLE
- TELEPHONE MANHOLE
- WATER MANHOLE
- SEWER MANHOLE
- BOULDER
- TREE STUMP
- CONIFEROUS TREE
- DECIDUOUS TREE
- CONIFEROUS SHRUB
- DECIDUOUS BUSH
- BORING
- PEDESTRIAN MAT
- CONCRETE
- LANDSCAPED AREA
- CRUSHED STONE
- BRICK
- TYPICAL EDGE OF PAVEMENT
- SINGLE WHITE LINE
- SINGLE YELLOW LINE
- DOUBLE YELLOW LINE
- CONCRETE
- VERTICAL GRANITE CURB
- SLOPED GRANITE CURB
- CONCRETE CURB
- BITUMINOUS BERM
- TAX MAP & LOT NUMBER
- FLOW LINES (ASSUMED)

NOTE:
 ALL ELECTRIC, GAS, TEL, WATER, SEWER AND DRAIN SERVICES ARE SHOWN IN SCHEMATIC FASHION. THEIR LOCATIONS ARE NOT
 PRECISE OR NECESSARILY ACCURATE. NOTICES OF WORKER SHALL BE INSTALLED ON THIS SITE USING THIS PLAN TO
 LOCATE THE ABOVE SERVICES. CONSULT WITH THE PROPER AUTHORITIES CONCERNED WITH THE SUBJECT SERVICE LOCATIONS.
 FOR INFORMATION REGARDING SUCH, CALL DIG-SAFE AT 811.



DATA SOURCES:
 BACKGROUND: GOOGLE EARTH IMAGERY, 2017
 TOPOGRAPHIC DATA: 2011 LIDAR FOR THE NORTHEAST

TEST PITS
 TEST PITS MUST BE
 CONDUCTED AT EACH LOCATION
 TO VERIFY SOILS AND
 SEASONAL HIGH WATER TABLE

This Drawing shall not be used
 for Construction unless Signed
 and Sealed For Construction.



BMP ID	SOIL CLASS (NRCS)	SOIL TYPE (NRCS)	HYDROLOGIC SOIL GROUP (NRCS)	HYDRAULIC CONDUCTIVITY (SSSNE)
MP1	SUFFIELD	SILT LOAM	C	0-0.2 IN/HR


MATERIAL LEGEND

- INFILTRATION CHAMBER
- BRICK SIDEWALK WITH PATTERN TO MATCH EXISTING
- CONCRETE SIDEWALK
- CONCRETE PAVING
- GRASS
- STANDARD "HMA" PAVEMENT
- BIORETENTION SWALE
- TREE PLANTER
- ROW - INFILTRATION GRASSED
- ROW INFILTRATION - TREE TRENCH

LEGEND - EXISTING
(EXISTING - SURVEYED AREAS)

- ABUTTERS LINE (PER TOWN OF EXETER GIS)
- STOCKADE FENCE
- PICKET FENCE
- POST & RAIL FENCE
- CHAIN LINK FENCE
- OVERHEAD WIRES
- SEWER LINE
- DRAIN LINE
- GAS LINE
- WATER LINE
- MAJOR CONTOUR LINE
- MINOR CONTOUR LINE
- TREE LINE
- SHRUB LINE
- UTILITY POLE & GUY WIRE
- SIGN
- GRANITE BOUND FOUND
- IRON PIPE/ROD FOUND
- POST
- FIRE HYDRANT
- WATER GATE VALVE
- WATER SHUTOFF VALVE
- GAS GATE VALVE
- GAS SHUTOFF VALVE
- GAS METER
- MAIL BOX
- CATCH BASIN (ROUND)
- CATCH BASIN
- DRAIN MANHOLE
- MANHOLE
- ELECTRIC MANHOLE
- TELEPHONE MANHOLE
- WATER MANHOLE
- SEWER MANHOLE
- BOULDER
- TREE STUMP
- CONIFEROUS TREE
- DECIDUOUS TREE
- CONIFEROUS SHRUB
- DECIDUOUS BUSH
- BORING
- PEDESTRIAN MAT
- CONCRETE
- LANDSCAPED AREA
- CRUSHED STONE
- BRICK
- TYPICAL EDGE OF PAVEMENT
- SINGLE WHITE LINE
- SINGLE YELLOW LINE
- DOUBLE YELLOW LINE
- CONCRETE
- VERTICAL GRANITE CURB
- SLOPED GRANITE CURB
- CONCRETE CURB
- BITUMINOUS BERM
- TAX MAP & LOT NUMBER
- FLOW LINES (ASSUMED)

NOTE: ALL ELECTRIC, GAS, TEL, WATER, SEWER AND DRAIN SERVICES ARE SHOWN IN SCHEMATIC FASHION. THEIR LOCATIONS ARE NOT PRECISE OR NECESSARILY ACCURATE. NO WORK WHATSOEVER SHALL BE UNDERTAKEN ON THIS SITE USING THIS PLAN TO LOCATE THE ABOVE SERVICES. CONSULT WITH THE PROPER AUTHORITIES CONCERNED WITH THE SUBJECT SERVICE LOCATIONS FOR INFORMATION REGARDING SUCH. CALL DIG-SAFE AT 811.



TEST PITS
TEST PITS MUST BE CONDUCTED AT EACH LOCATION TO VERIFY SOILS AND SEASONAL HIGH WATER TABLE

DATA SOURCES:
BACKGROUND: GOOGLE EARTH IMAGERY, 2017
TOPOGRAPHIC DATA: 2011 LIDAR FOR THE NORTHEAST

This Drawing shall not be used for Construction unless Signed and Sealed For Construction.

NO	DATE	DESCRIPTION	CHK
1	11/7/18	30% DESIGNS	RR

WATERSTONE ENGINEERING
INNOVATIVE SUSTAINABLE WATER MANAGEMENT
9 GRETA'S WAY
STRATHAM, NH 03865
(P) 603.686.2488

30% BMP EXAMPLE DESIGNS
FOR THE DURHAM, NH MILL POND STUDY
MILL POND
NUTRIENT CONTROL MEASURES


PREPARED FOR:
TOWN OF DURHAM
8 NEWMARKET ROAD
DURHAM, NH 03824

DESIGNED BY: RR
DRAFTED BY: JS
CHECKED BY: RR

MILL POND ROAD
BMP - MP1


JOB #: 171006
SCALE: AS SHOWN
CONTRACT #: N/A
SHEET #: 6






- NOTES:
1. BIORETENTION SOIL MIX SHALL CONSIST OF 40% LOAM, 60% SAND.
 2. DO NOT COMPACT SUBGRADE AT BOTTOM OF EXCAVATION.
 3. NO BIORETENTION SOIL MIX SHALL BE PLACED UNTIL AFTER ENGINEERING APPROVAL AND INSPECTION OF SUBGRADE.
 4. GRAVEL RESERVOIR SHALL BE 1/2" TO 3" STONE WITH 40% VOIDS, ALTERNATIVES ACCEPTABLE UPON APPROVAL.
 5. GRASS SEED MIX SHALL BE NEW ENGLAND NATIVE WARM SEASON GRASS MIX WITH A BLEND OF COOL SEASON GRASSES INCLUDED AS A "STARTER" SEED FOR EROSION CONTROL. SPECIES: LITTLE BLUESTEM (SCHIZACHYRIUM SCOPARIUM), BIG BLUESTEM (ANDROPOGON GERARDII), VIRGINIA WILD RYE (ELYMUS VIRGINICUS), INDIAN GRASS (SORGHASTRUM NUTANS), RED FESCUE (FESTUCA RUBRA), SWITCH GRASS (PANICUM VIRGATUM), APPLICATION RATE: 23 LBS/ACRE | 1900 SQ FT/LB

BIOSWALE SYSTEM - TYPICAL
B-B' CROSS-SECTION
 NOT TO SCALE




- NOTES:
1. PRETX DEEP SUMP HOODED CATCH BASIN SYSTEMS BY ACF


PRETREATMENT CATCH BASIN
PLAN VIEW
 NOT TO SCALE



PRETREATMENT-BIOSWALE COMBINATION
A-A' CROSS SECTION
 NOT TO SCALE




PRETX CURB DETAILS
 NOT TO SCALE



PRETREATMENT CATCH BASIN OUTLET TO
BIORETENTION CONFIGURATION
 NOT TO SCALE

- NOTES:
1. SEE DRAINAGE PLAN FOR STRUCTURE ELEVATION AND INVERTS, PIPE TYPE, LENGTH AND SLOPE, AND BIORETENTION AREA DIMENSIONS.



- NOTES:
1. PRETX DEEP SUMP HOODED CATCH BASIN SYSTEMS BY ACF ARE A PRE-FILTER AND CRITICAL MAINTENANCE DEVICE THAT EXTENDS THE OPERATING LIFE AND REDUCES THE MAINTENANCE BURDEN OF BIORETENTION SYSTEMS, RAIN GARDENS, AND BIOSWALES BY FILTERING OUT SEDIMENT, TRASH AND DEBRIS AT THE INLET.

PRETREATMENT CATCH BASIN
INLET DETAIL
 NOT TO SCALE

This Drawing shall not be used for Construction unless Signed and Sealed For Construction.

NO	DATE	DESCRIPTION	CHKD
1	11/7/18	30% DESIGNS	RR

WATERSTONE ENGINEERING
 INNOVATIVE SUSTAINABLE WATER MANAGEMENT

8 GRETA'S WAY
 STRATFORD, NH 03885
 (P) 603.866.2468

30% BMP EXAMPLE DESIGNS
 FOR THE DURHAM, NH MILL POND STUDY

MILL POND
NUTRIENT CONTROL MEASURES


PREPARED FOR:
 TOWN OF DURHAM
 8 NEWMARKET ROAD
 DURHAM, NH 03824

DESIGNED BY: RR
 DRAFTED BY: JS
 CHECKED BY: RR

DRAINAGE DETAILS


JOB #: 171006
 SCALE: AS SHOWN
 CONTRACT #: N/A
 SHEET #: 7

D1




- NOTES:**
1. BIORETENTION SOIL MIX SHALL CONSIST OF 40% LOAM, 60% SAND.
 2. DO NOT COMPACT SUBGRADE AT BOTTOM OF EXCAVATION.
 3. NO BIORETENTION SOIL MIX SHALL BE PLACED UNTIL AFTER ENGINEERING APPROVAL AND INSPECTION OF SUBGRADE.
 4. GRAVEL RESERVOIR SHALL BE 1/2" TO 3" STONE WITH 40% VOIDS, ALTERNATIVES ACCEPTABLE UPON APPROVAL.
 5. GRASS SEED MIX SHALL BE NEW ENGLAND NATIVE WARM SEASON GRASS MIX WITH A BLEND OF COOL SEASON GRASSES INCLUDED AS A "STARTER" SEED FOR EROSION CONTROL. SPECIES: LITTLE BLUESTEM (SCHIZACHYRIUM SCOPARIUM), BIG BLUESTEM (ANDROPOGON GERARDII), VIRGINIA WILD RYE (ELYMUS VIRGINICUS), INDIAN GRASS (SORGHASTRUM NUTANS), RED FESCUE (FESTUCA RUBRA), SWITCH GRASS (PANICUM VIRGATUM).
 6. APPLICATION RATE: 23 LBS/ACRE | 1900 SQ FT/LB.

BIOSWALE SYSTEM - TYPICAL B-B' CROSS-SECTION
NOT TO SCALE




- NOTES:**
1. PRETX DEEP SUMP HOODED CATCH BASIN SYSTEMS BY ACF


PRETREATMENT CATCH BASIN PLAN VIEW
NOT TO SCALE



PRETREATMENT-BIOSWALE COMBINATION A-A' CROSS SECTION
NOT TO SCALE




PRETX CURB DETAILS
NOT TO SCALE



PRETREATMENT CATCH BASIN OUTLET TO BIORETENTION CONFIGURATION
NOT TO SCALE

- NOTES:**
1. SEE DRAINAGE PLAN FOR STRUCTURE ELEVATION AND INVERTS, PIPE TYPE, LENGTH AND SLOPE, AND BIORETENTION AREA DIMENSIONS.



- NOTES:**
1. PRETX DEEP SUMP HOODED CATCH BASIN SYSTEMS BY ACF ARE A PRE-FILTER AND CRITICAL MAINTENANCE DEVICE THAT EXTENDS THE OPERATING LIFE AND REDUCES THE MAINTENANCE BURDEN OF BIORETENTION SYSTEMS, RAIN GARDENS, AND BIOSWALES BY FILTERING OUT SEDIMENT, TRASH AND DEBRIS AT THE INLET.

PRETREATMENT CATCH BASIN INLET DETAIL
NOT TO SCALE

NO	DATE	DESCRIPTION	CHKD
1	11/7/18	30% DESIGNS	RR

WATERSTONE ENGINEERING
INNOVATIVE ENVIRONMENTAL MANAGEMENT
9 GRETA'S WAY
STRATFORD, NH 03885
(P) 603.666.2466


30% BMP EXAMPLE DESIGNS
FOR THE DURHAM, NH MILL POND STUDY
NUTRIENT CONTROL MEASURES

PREPARED FOR:
TOWN OF DURHAM
8 NEWMARKET ROAD
DURHAM, NH 03824
DESIGNED BY: RR
DRAFTED BY: JS
CHECKED BY: RR


MADBURY ROAD BMP - MR1
JOB #: 171006
SCALE: AS SHOWN
CONTRACT #: N/A
SHEET #: 8

D2

This Drawing shall not be used for Construction unless Signed and Sealed For Construction.



PLAN
CULTEC RECHARGER® 330
STORMWATER MANAGEMENT SYSTEM
 NOT TO SCALE




A SECTION
 D3 SCALE: NOT TO SCALE

CULTEC RECHARGER® 330 XLHD LEGEND

- RECHARGER 330XLSDH STARTER
- RECHARGER 330XLHD INTERMEDIATE
- RECHARGER 330XLEHD END
- CULTEC NO. 66 WOVEN GEOTEXTILE
- CULTEC NO. 410 NON-WOVEN GEOTEXTILE


TEST PITS

TEST PITS MUST BE CONDUCTED AT EACH LOCATION TO VERIFY SOILS AND SEASONAL HIGH WATER TABLE



1 INSPECTION PORT DETAIL
 D3 NOT TO SCALE

MATERIALS LIST		
(SEE COVER SHEET FOR COMBINED PROJECT MATERIALS LIST)		
RECHARGER 330XLSDH STARTER		PIECES
RECHARGER 330XLHD INTERMEDIATE		PIECES
RECHARGER 330XLEHD END		PIECES
CULTEC NO. 66 WOVEN GEOTEXTILE 7.5' x 300'		LINEAL FEET
SEPARATOR ROW MATERIALS LIST		
CULTEC NO. 410 NON-WOVEN GEOTEXTILE 7.5' x 300' (TO WRAP SEPARATOR ROW)		SQ. YDS
CULTEC NO. 66 WOVEN GEOTEXTILE 7.5' x 300' (BENEATH SEPARATOR ROW)		ROLLS



B SECTION
 D3 SCALE: NOT TO SCALE

NOTES:
 1. ALL ELECTRIC, GAS, TEL, WATER, SEWER AND DRAIN SERVICES ARE SHOWN IN SCHEMATIC FASHION, THEIR LOCATIONS ARE NOT PRECISE OR NECESSARILY ACCURATE. NO WORK WHATSOEVER SHALL BE UNDERTAKEN ON THIS SITE USING THIS PLAN TO LOCATE THE ABOVE SERVICES. CONSULT WITH THE PROPER AUTHORITIES CONCERNED WITH THE SUBJECT SERVICE LOCATIONS FOR INFORMATION REGARDING SUCH. CALL DIGSAFE AT 811.
 2. UNDERGROUND UTILITIES SHOWN ARE APPROXIMATE. EXACT LOCATIONS OF EXISTING UNDERGROUND UTILITIES SHALL BE DETERMINED BY THE CONTRACTOR IN THE FIELD PRIOR TO CONSTRUCTION.

This Drawing shall not be used for Construction unless Signed and Sealed For Construction.

NO	DATE	DESCRIPTION	CHKD
1	11/7/18	30% DESIGNS	RR

WATERSTONE ENGINEERING
 INNOVATIVE & SUSTAINABLE WATER MANAGEMENT
 9 GRETA'S WAY
 STRATHAM, NH 03885
 (P) 603.686.2488

30% BMP EXAMPLE DESIGNS
FOR THE DURHAM, NH MILL POND STUDY
MILL POND
NUTRIENT CONTROL MEASURES

PREPARED FOR:
 TOWN OF DURHAM
 8 NEWMARKET ROAD
 DURHAM, NH 03824

DESIGNED BY: RR
 DRAFTED BY: JS
 CHECKED BY: RR







MILL POND ROAD BMP - MP1

JOB #: 171006
 SCALE: AS SHOWN
 CONTRACT #: N/A
 SHEET #: 9

D3

PRETX SPECIFICATIONS

- A. GENERAL**
- PRETX SYSTEMS ARE A PRE-FILTER AND CRITICAL MAINTENANCE DEVICE THAT EXTENDS THE OPERATING LIFE AND REDUCES THE MAINTENANCE BURDEN OF BIORETENTION SYSTEMS, RAIN GARDENS, BIOSWALES AND OTHER TYPES OF SURFACE BEST MANAGEMENT PRACTICES BY FILTERING OUT SEDIMENT, TRASH AND DEBRIS AT THE INLET.
- B. PRODUCTS**
- PRETX IS AVAILABLE IN 3 MODELS THAT MANAGE MOST BIORETENTION INLET CONFIGURATIONS: CURB, DROP, AND INLINE.
 - PRETX-CURB IS FOR EDGE OF PAVEMENT RUNOFF AT A CURB CUT IN LIEU OF A STONE SPREADER.
 - PRETX-DROP IS FOR USE AS A DROP INLET CONFIGURATION ALONG A CURB LINE AND WOULD BE INSTALLED WITH A STANDARD DROP INLET GRATE.
 - PRETX-INLINE IS FOR USE WITH SUBSURFACE INLET AND OUTLET PIPE.
 - PRETX IS SIZED TO PRETREAT WATER QUALITY FLOWS AND BYPASS LARGER FLOWS THAT HAVE MINIMAL TRASH AND DEBRIS. PRETX CAN BE USED BOTH IN RETROFIT OR NEW INSTALLATIONS.
 - ACCEPTABLE SYSTEM SUPPLIER:
CONVERGENT WATER TECHNOLOGIES, INC. OR ITS AUTHORIZED VALUE-ADDED RESELLER
(800) 711-5428
WWW.CONVERGENTWATER.COM
- C. SUBMITTALS**
- SUBMIT PROPOSED LAYOUT DRAWINGS. DRAWINGS SHALL INCLUDE TYPICAL SECTION DETAILS ANNOTED WITH SYSTEM ELEVATIONS (E.G., RIM, PIPE INVERTS, OUTSIDE BOTTOM OF STRUCTURE, ETC.).
 - SUBMIT MATERIAL CERTIFICATES FOR FRAMES AND COVERS
 - ANY PROPOSED EQUAL ALTERNATE PRODUCT SUBSTITUTION TO THIS SPECIFICATION MUST BE SUBMITTED FOR REVIEW AND APPROVED PRIOR TO BID OPENING.
- D. EXECUTION**
- ALL PUBLIC STORM DRAINAGE SYSTEMS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE LATEST EDITION OF THE STATE DEPARTMENT OF TRANSPORTATION STANDARDS AND SPECIFICATIONS AND ACCORDING TO LOCAL MUNICIPAL REQUIREMENTS.
 - ALL STORM DRAINAGE SYSTEM CONSTRUCTION IS SUBJECT TO INSPECTION AND APPROVAL BY THE PROJECT ENGINEER.
 - THE CONTRACTOR SHALL NOTIFY THE PROJECT ENGINEER A MINIMUM OF TWO FULL BUSINESS DAYS PRIOR TO THE START OF CONSTRUCTION.
 - THE CONTRACTOR SHALL BE RESPONSIBLE FOR CONTACTING AND OBTAINING APPROVAL FROM DIG-SAFE AND DETERMINING THE LOCATION OF ALL UNDERGROUND UTILITIES PRIOR TO THE START OF CONSTRUCTION/ EXCAVATION AND SHALL NOTIFY THE PROJECT ENGINEER OF ANY POTENTIAL CONFLICTS.
 - TO PROTECT STORMWATER FLOW CONTROL AND QUALITY TREATMENT FACILITIES FROM SEDIMENTATION, THEY SHALL BE CONNECTED TO THE STORM CONVEYANCE SYSTEM ONLY AFTER ALL SITE WORK, ROAD CONSTRUCTION, UTILITY WORK AND LANDSCAPING ARE IN PLACE IN ALL AREAS ABOVE AND UPSTREAM OF THE FACILITY.
 - THE EXISTING STORM SEWER SYSTEM SHALL STAY ISOLATED FROM THE NEW SYSTEM UNTIL THE NEW SYSTEM IS CLEANED, AND APPROVED FOR USE. THERE SHALL BE NO DEBRIS IN THE LINES OR FURTHER CLEANING WILL BE REQUIRED PRIOR TO ACCEPTANCE.
 - PROVIDE A 1.5" MINIMUM GAP BETWEEN THE KNOCKOUT WALL AND THE OUTSIDE OF THE PIPE. AFTER THE PIPE IS INSTALLED, FILL THE GAP WITH JOINT MORTAR.
 - THE OPENING SHALL BE MEASURED AT THE TOP OF THE PRECAST BASE SECTION.
 - ALL PICKUP HOLES SHALL BE GROUTED FULL AFTER THE BASIN HAS BEEN PLACED.
 - STANDARD CURB INLETS AND TIPDOWNS SHALL BE PRECAST CONCRETE OR ASPHALT.
 - PIPE ENDS SHALL BE FLUSH WITH THE INNER WALL OR 1" MAXIMUM INTRUSION. MASONRY, CINDER BLOCKS, OR SIMILAR MATERIALS MAY BE USED TO ADJUST THE RISERS TO GRADE PRIOR TO GROUTING.
 - GROUTING SHALL BE SUFFICIENT TO PREVENT LEAKS BETWEEN THE PRECAST COMPONENTS OF THE COMPLETED STRUCTURE & SHALL BE PERFORMED INSIDE, BETWEEN & OUTSIDE OF ALL RISERS, JOINTS & PIPE PENETRATIONS.
 - MANHOLES TO BE CONSTRUCTED IN ACCORDANCE WITH AASHTO M-199 UNLESS OTHERWISE SHOWN ON PLANS OR NOTED IN THE STANDARD SPECIFICATIONS.
 - ALL REINFORCED CAST IN PLACE CONCRETE SHALL BE CLASS 4000. ALL PRECAST CONCRETE SHALL BE CLASS 4000.
 - RECAST BASES SHALL BE FURNISHED WITH CUTOUTS OR KNOCKOUTS. KNOCKOUTS SHALL HAVE A WALL THICKNESS OF 2" MINIMUM.
 - MATING SURFACES OF MANHOLE RINGS AND COVERS SHALL BE FINISHED TO ASSURE NON-ROCKING FIT WITH ANY COVER POSITIONS.
- E. CONSTRUCTION AND SEQUENCING**
- EXAMINATION
 - VERIFY LAYOUT AND ORIENTATION OF PRE-TX SYSTEM AREA INCLUDING EDGE OF PAVEMENT, TIP DOWN, CURBS AND SIDEWALK, BIOFILTRATION SYSTEM, AND CONNECTIONS.
 - VERIFY EXCAVATION BASE IS READY TO RECEIVE WORK AND EXCAVATIONS, DIMENSIONS, AND ELEVATIONS ARE AS INDICATED ON DRAWINGS.
 - PREPARATION
 - CALL DIG SAFE AND RECEIVE APPROVAL BEFORE PERFORMING WORK.
 - REQUEST UNDERGROUND UTILITIES TO BE LOCATED AND MARKED WITHIN AND SURROUNDING CONSTRUCTION AREAS.
 - IDENTIFY REQUIRED LINES, LEVELS, CONTOURS, AND DATUM.
 - CLEAR AND GRUB THE PROPOSED PRE-TX SYSTEM AREA.
 - EXCAVATION AND INSTALLATION
 - THE FOLLOWING CONSTRUCTION SEQUENCE IS TO BE USED AS A GENERAL GUIDELINE. COORDINATE WITH THE OWNER, AND ENGINEERS FOR REVIEW AND APPROVAL PRIOR TO CONSTRUCTION.
 - INSTALL TEMPORARY EROSION AND SEDIMENT CONTROLS TO DIVERT STORM WATER AWAY FROM THE PRE-TX SYSTEM AREA.
 - EXCAVATE TO THE BOTTOM INVERT OF THE SYSTEM.
 - TO MINIMIZE COMPACTION OF ADJACENT BIOFILTRATION SYSTEMS, WORK EXCAVATORS OR BACKHOES FROM THE SIDES TO EXCAVATE THE PRE-TX SYSTEM AREA TO ITS APPROPRIATE DESIGN DEPTH AND DIMENSIONS.
 - ROUGH GRADE THE PRE-TX SYSTEM AREA DURING GENERAL CONSTRUCTION. EXCAVATE THE PRE-TX SYSTEM FACILITIES TO WITHIN 1 FOOT OF STRUCTURE BOTTOM.
 - PLACE 1 FOOT BED OF COARSE STONE TO ELEVATION OF BASE OF STRUCTURE.
 - ESTABLISH ELEVATIONS FOR ADJACENT CURBS, EDGE OF PAVEMENT AND TIP DOWN, SIDEWALK, PIPE INVERTS FOR INLETS AND OUTLETS AS INDICATED ON DRAWINGS.
 - INSTALLATION
 - PLACE THE PRECAST SYSTEM TO NECESSARY ELEVATION.
 - VERIFY ELEVATIONS FOR ADJACENT CURBS, EDGE OF PAVEMENT, PAVEMENT GRADING FOR INLET GRATE FOR PRETX-DROP, SIDEWALK, PIPE INVERTS FOR INLETS AND OUTLETS, OUTLET INVERT FOR KNEE WALL.
 - FOR PRETX-SURFACE:
 - VERIFY ELEVATIONS FOR ADJACENT CURBS.
 - VERIFY EDGE OF PAVEMENT TIP DOWN PAVEMENT GRADING FOR INLET GRATE.
 - VERIFY CURB ELEVATION IN RELATION TO PAVEMENT AND TIP DOWN.
 - VERIFY OUTLET INVERT FOR KNEE WALL IN RELATION TO FILTER MEDIA.
 - FOR PRETX-DROP:
 - VERIFY ALL INLET PIPES ENTER THE STRUCTURE UPSTREAM OF BAFFLE.
 - VERIFY FRAME AND GRATE OFFSET ON INLET SIDE AND UPSTREAM OF BAFFLE.
 - VERIFY CURB LOCATION WITH RESPECT TO FRAME AND GRATE ORIENTATION.
 - INSTALL BAFFLES, WEIR, AND SCREENS AS INDICATED ON DRAWINGS.
 - VERIFY MAINTENANCE ACCESS THROUGH GRATE OR COVER AND CLEARANCE FOR VACTOR.
 - INSTALL TOP OF STRUCTURE LEVEL WITH ADJACENT CURB OR SIDEWALK AS PER MANUFACTURERS SPECIFICATIONS. ENGINEER FIELD VISIT REQUIRED PRIOR TO BACKFILLING.
- F. PRECAST AND STRUCTURE ALIGNMENT**
- ALIGNMENT
 - INLET SIDE AND LOCATION OFFSET GRATE TO BE ALIGNED WITH CURB.
 - GRATE AND INLINE PIPES MUST ENTER UPSTREAM OF BAFFLE.
 - STANDARD HEAVY DUTY FRAME AND GRATE 24" X 24"
 - PICK WEIGHT APPROX.: TOP SLAB = 1,850 LBS BASE = 7,178 LBS
 - CONCRETE: 4,000 PSI MINIMUM AFTER 28 DAYS HS-20 DESIGN LOADING PER AASHTO HS-20-44 ASTM C478 SPEC FOR PRECAST REINFORCED CONCRETE MH SECTIONS
 - BAFFLES:
 - B1 - 3/4" HDPE
 - B2 - 3/4" HDPE
 - B3 - .5" X 13 GA EXPANDED SS SHEET



NO	DATE	DESCRIPTION	CHK
1	11/17/18	30% DESIGNS	RR

WATERSTONE ENGINEERING
INNOVATIVE STORMWATER MANAGEMENT

9 GRETA'S WAY
STRATHAM, NH 03865
(p) 603.666.2488

**30% BMP EXAMPLE DESIGNS
FOR THE DURHAM, NH MILL POND STUDY
MILL POND
NUTRIENT CONTROL MEASURES**

PREPARED FOR:
TOWN OF DURHAM
8 NEWMARKET ROAD
DURHAM, NH 03824

DESIGNED BY:	RR
DRAFTED BY:	JS
CHECKED BY:	RR

PRETREATMENT DETAILS

JOB #:	171006
SCALE:	AS SHOWN
CONTRACT #:	N/A
SHEET #:	10

D4

This Drawing shall not be used for Construction unless Signed and Sealed For Construction.

APPENDIX B: POLLUTANT LOAD AND COSTING METHODOLOGY

Pollutant Loading and BMP Costing Analysis

A planning level pollutant loading and BMP costing analysis was performed for each of the 7 potential BMPs identified for the Lincoln Street watershed. The soil type, BMP type, and land use type for each BMP is shown in Table 1 - BMP type, soil, and land use summary. These were used in conjunction with performance curves from the WISE, 2015¹ analysis to determine expected runoff and nitrogen load reductions associated with each BMP.

These curves and associated pollutant load reduction estimates are shown in Section C.1, below.

Estimates for the cost per acre of drainage area for each BMP type from the WISE, 2015¹ analysis were used to estimate the total and unit costs associated with the nitrogen load reductions for each BMP. The numbers used for these estimates are shown in Section C.2, below.

Table 1 - BMP type, soil, and land use summary

BMP Location	Soil Type	Proposed BMP Type
1	A	Subsurface Infiltration
2	A	Subsurface Infiltration
3.1	A	Bioretention
3.2	A	Bioretention
3.3 - 3.6	A	Bioretention
4	A	Subsurface infiltration
5	A	Subsurface infiltration
6	C	Bioretention
7	A	Subsurface Infiltration

¹ Roseen, R., Watts, A., Bourdeau, R., Stacey, P., Sinnott, C., Walker, T., Thompson, D., Roberts, E., and Miller, S. (2015). Water Integration for Squamscott Exeter (WISE), Preliminary Integrated Plan, Final Technical Report. Portsmouth, NH, Geosyntec Consultants, University of New Hampshire, Rockingham Planning Commission, Great Bay National Estuarine Research Reserve, Consensus Building Institute.

C.1 Pollutant Loading Analysis

Pollutant Loading Calculation Example


The following example and accompanying figures explain the approach taken for the pollutant loading and volume reduction analysis performed in this study with a BMP of the following characteristics:

- subsurface infiltration system,
- 1" water quality volume,
- type B soil,
- commercial land use,

From the BMP performance curve for a subsurface infiltration system pollutant removal and volume reduction are determined as follows:

1. **Determine initial load.** Where the BMP curve for nitrogen (black curves) crosses the left hand vertical axis (capture depth=0) determine the initial TN load based on commercial land use = 13.3 lbs/ac/yr.
2. **Determine treated load.** Locate performance curve for soil type B for the capture volume. A system treating a 1" water quality volume for 1 acre will have a treated load of 2.3 lbs/ac/yr.

Example 1: BMP optimization for pollutant load with subsurface infiltration at 1" water quality volume




3. **Determine load removed.** An initial load of 13.3 lbs/ac/yr and a treated load of 2.3 lbs/ac/yr removes 11 lbs/ac/yr or 83% annual TN reduction.

$$\frac{\text{Treated Load}}{\text{Initial Load}} = \frac{11}{13.3} = 83\% \text{ TN reduction annually}$$

4. **Determine initial runoff volume.** Where the BMP curve for volume (blue curves) crosses the left hand vertical axis (capture depth=0) determine the initial runoff volume based on the right hand axis for commercial land use = 0.9 million gallons/ac/yr.
5. **Determine treated runoff volume.** Locate performance curve for soil type B for the capture volume. A system treating a 1" water quality volume for 1 acre will have a runoff volume = 0.11 million gallons/ac/yr.

Example 2: BMP optimization for volume with subsurface infiltration at 1" water quality volume



6. **Determine volume removed.** An initial runoff volume of 0.9 MG/ac/yr and a treated runoff volume of 0.11 MG/ac/yr removes 0.79 MG/ac/yr or 88% annual runoff reduction.

$$\frac{\text{Treated Runoff Volume}}{\text{Initial Runoff Volume}} = \frac{0.11}{0.9} = 88\% \text{ runoff volume reduction annually}$$

The complete methods can be found in the BMP Decision Support System (BMPDSS)(EPA 2010)² and WISE Project (Roseen et al 2015)¹. This approach was developed in cooperation with EPA Region 1 to support an Integrated Planning and Permitting framework for watershed scale nitrogen management for the Exeter-Squamscott Watershed.

² EPA and I. Tetra Tech (2010). Stormwater Best Management Practices (BMP) Performance Analysis. United States Environmental Protection Agency – Region 1, Boston, MA.

The following tables display the actual numbers used to calculate pollutant load reductions in this analysis, applying the methodology outlined above in Examples 1 and 2. The associated BMP performance curves can be found in WISE, 2015¹, pages 92-180.

Table 2 - Performance estimates for BMP 6

BMP	Drainage Area (acres)	Annual N Load (lbs)	1/4" Volume Reduction (ft ³)	1/2" Volume Reduction (ft ³)	1/4" N Reduction (lbs)	1/2" N Reduction (lbs)
6	1.73	27.27	1,569	3,138	5	6

Table 3 - Performance estimates for BMP 3

BMP	Drainage Area (acres)	Annual N Load (lbs)	1/4" Volume Reduction (ft ³)	1/2" Volume Reduction (ft ³)	1/4" N Reduction (lbs)	1/2" N Reduction (lbs)
3	12.33	104.64	11,192	22,384	65	84

Table 4 - Performance estimates for BMPs 1, 2, 4, 5, and 7

BMP	Drainage Area (acres)	Annual N Load (lbs)	1/4" Volume Reduction (ft ³)	1/2" Volume Reduction (ft ³)	1/4" N Reduction (lbs)	1/2" N Reduction (lbs)
1	11.15	76.6	10,116	20,232	42	62
2	24.56	157.6	22,291	44,582	84	120
4	38.63	252.2	35,059	70,119	114	174
5	17.85	113.7	16,199	32,397	59	86
7	24.79	152.3	22,498	44,997	77	113



C.2 COSTING ANALYSIS

The WISE, 2015³ study developed estimates for the cost of sizing a variety of stormwater capture systems to manage different size storm events. Table 5 - BMP cost estimates developed for WISE, 2015 shows the estimated per-acre costs for bioretention and subsurface infiltration systems designed to manage the 0.25" and 0.5" storm events.

In order to calculate the total cost of a BMP using this table, it is necessary to multiply the drainage area by the cost shown in Table 5 - BMP cost estimates developed for WISE, 2015. The unit cost (\$ per pound of nutrient load reduction) can then be derived by dividing the total cost by the total expected annual nutrient load reduction.

Table 5 - BMP cost estimates developed for WISE, 2015

Structural Treatment Practice	Capitol Cost Range Based on Capture Depth of 1-acre drainage area (\$)					
	0.25 in.			0.5 in.		
	LOW	HIGH	FINAL	LOW	HIGH	FINAL
Bioretention with Underdrain (No Pretreatment) ¹	\$2,759	\$40,000	\$11,400	\$5,518	\$60,000	\$18,300
Subsurface Infiltration	\$18,000	\$35,000	\$18,500	\$25,000	\$45,000	\$28,000

1. Pretreatment not required for direct runoff from impervious surfaces (i.e., roof tops and parking lots).

³ Roseen, R., Watts, A., Bourdeau, R., Stacey, P., Sinnott, C., Walker, T., Thompson, D., Roberts, E., and Miller, S. (2015). Water Integration for Squamscott Exeter (WISE), Preliminary Integrated Plan, Final Technical Report. Portsmouth, NH, Geosyntec Consultants, University of New Hampshire, Rockingham Planning Commission, Great Bay National Estuarine Research Reserve, Consensus Building Institute.

BMP Cost Calculation Example

The following example explains the approach taken for the costing analysis performed in this study using BMP 1, which has the the following relevant characteristics:

- subsurface infiltration system,
- 0.25” water quality volume,
- 11.1 acre drainage area
- 42 lbs annual Nitrogen load reduction when sized for 0.25” water quality volume (from Pollutant Loading Analysis)

1. Reference Table 5 to determine the capital cost per-acre for a subsurface infiltration system sized to capture the 0.25” water quality volume. For this analysis, we use the ‘Final’ estimate rather than the ‘High’ or ‘Low’ estimates, yielding a per-acre cost of \$18,500.

2. Multiply the per-acre cost by the BMP drainage area. For BMP 1, the drainage area is 11.1 acres:
 $[11.15 \text{ acres}] \times [\$18,500 / \text{acre}] = \$206,221$

3. Divide the total cost from Step 2 by the annual Nitrogen Load reduction potential to derive the unit cost for the BMP:

$$[\$206,206] / [42 \text{ lbs N}] = \$4,905 / \text{lb N}$$

Table 6 – Lincoln Street costing analysis results, shows the results of this analysis applied to the Lincoln Street watershed.

Table 6 – Lincoln Street costing analysis results

BMP Location	Drainage Area (acres)	1/4" WQV System		1/2" WQV System	
		Total Cost	Unit Cost (\$/lb)	Total Cost	Unit Cost (\$/lb)
1	11.1	\$206,221	\$4,900	\$312,118	\$5,000
2	24.6	\$454,414	\$5,400	\$687,761	\$5,700
3.1	6.9	\$78,509	\$2,200	\$126,028	\$2,700
3.2	4.2	\$47,512	\$2,500	\$76,270	\$3,100
3.3 - 3.6	1.3	\$14,569	\$1,400	\$23,388	\$1,800
4	38.6	\$714,710	\$6,300	\$1,081,724	\$6,200
5	17.9	\$330,222	\$5,600	\$499,796	\$5,800
6	1.7	\$19,713	\$3,800	\$31,644	\$5,000
7	24.8	\$458,646	\$5,900	\$694,167	\$6,100